FI	LE	MO	iAT	IONS
----	----	----	-----	------

Control of the Contro

Enterned in NID File the red On S.R. Sheet Location Map Pinned	+	Checked by Chief Copy NID to Field Office Approval Letter	PHD
Card Indexed		Disapproval Letter	-
IWR for State or Fee Land			
COMPLETION DATA	<b>\</b> :		
Date Well Completed	*	Location Inspected	***************************************
OW WW	PA	Bond released State of Fee Land	
	LOGS FIL	ED '	
Drilor's Log			
Electric Logs (No.	1-4		
E I	E-1	R. GR-N.	Aicro
Lat N	Mi-LSonic	Others	•••••

RESIDENCE INTELLIGENCE STATE OF THE SECRETARIES

4/





#### Budget Bureau No. 42-R356.5 Approval expires 12-31-60

#### UNITED STATES

#### DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

LAND OFFICE			.4
Lease Number			
Unit	Clay	Basin	

#### LESSEE'S MONTHLY REPORT OF OPERATIONS

State	·	Vte	ıh		Cou	nty Dag	gett		Field	C1	ay Basin			
	T	be f	ollowin	g is	a corre	ect report o	f opera	tions an	$d$ $p_1$	roduction	(including	drilling	and	produci
					P.	O. Box 989			Comi	bany MOU	NTAIN F	EL SUP	PLY C	COMPAN
					Salt 1	LAKE CITY, UT	АН		Signe	d!	ゴル	nee	ly	
Phon	ie					328-8315			Agen	t's title [	IVISIONA	CHIEF	ACC	DUNTAI
SEC.	AND F 1/4	TWP.	RANGE	WELL No.	DAYS PRODUCED	BARRELS OF OIL	GRAVITY	Cu. Ft. Of (In thousa	GAS nds)	GALLONS OF GASOLINE RECOVERED	BARRELS OF WATER (If none, so state)	(If drilling	REMAR , depth; and res e conten	KS if shut do ult of test f it of gas)
<b>184</b>	22	3	) **	lay i	Casin	Unix						Loca	tion	
										÷				
														;
							-		-					


NOTE.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor.



# SUBMIT IN TRIPLICATE\* (Other instructions on reverse side)

#### STATE OF UTAH

	. & GAS CONSER	VATION COMMIS	SSION	1	5. LEASE DESIGNATION AND SERIAL N
					SL 04505LA  6. IF INDIAN, ALLOTTEE OR TRIBE NAM
APPLICATIO	N FOR PERMIT	TO DRILL, DEEP	EN, OR PLUG	BACK	O. IF INDIAN, ALLOTTER OR TRIBE NAS
. TYPE OF WORK	11 1 <del>1</del>	DEEPEN 🗌	PLUG BA	CK [	7. UNIT AGREEMENT NAME
UK . TYPE OF WELL	ILL XX	DEEPEN L	PLUG BA	.CR	Clay Basin
OIL G	VELL X OTHER		INGLE MULTI	PLE	8. FARM OR LEASE NAME
NAME OF OPERATOR	VELL LAI OTHER	VII aca o z	ONE ZONE		R. D. Murphy
	G	_		-	9. WELL NO.
OUNTAIN FUEL ADDRESS OF OPERATOR	. Supply Compan				7
				-	10. FIELD AND POOL, OR WILDCAT
P. 0. Box 112	Seport location clearly ar	d in accordance with any	State requirements.*)		Clay Basin-wildcat (Fro
At surface		1/	•	<u> </u>	11. SEC., T., R., M., OR BLK.
2210' FSL, 2	099' FEL, NW M			ļ	AND SURVEY OR AREA
At proposed prod. zon	ne same 70%	4 te for booth -	- Son Hark		22-3N-24E., SLB&M
DISTANCE IN MILES		AREST TOWN OR POST OFFIC			12. COUNTY OR PARISH   13. STATE
					Daggett Utah
DISTANCE FROM PROF	h of Rock Sprin		O. OF ACRES IN LEASE		F ACRES ASSIGNED
LOCATION TO NEARES PROPERTY OR LEASE LIS	sr (19 ±±0)	n SL 045051   36. N		TO TH	IS WELL
(Also to nearest drlg	g. line. if any)	10 70	640 ROPOSED DEPTH		Y OR CABLE TOOLS
		)U 10111   11111			
OR APPLIED FOR, ON TH		. 6-W	5600 t	RO	tary
	hether DF, RT, GR, etc.)				·
Ground 6	06221				April 20,1964
		PROPOSED CASING AND	D CEMENTING PROGR	AM	
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH		QUANTITY OF CEMENT
12-1/4	0. 5/0	-	· · · · · · · · · · · · · · · · · · ·		
	I 9 <del>-</del> 5/0	1 .36 & 40	1000	519 s	acks
7 <b>-</b> 5/8	9-5/8 4-1/2	36 & 40	1000 5650	519 s To be	acks determined
7-5/8  The surface h casing is cem gas as a circ  This will be from the Dako an existing g	4-1/2 nole will be drented, the well a wildcat well that formation.	illed with mud a l will be deepen to test the Fro Although this will dicated in Rule	s a circulatin ed to total de ntier formatio ell is located	To be g medium pth of 5 n. Exis less th	determined  After surface 650', using natural sting production is an 4960 feet from
The surface he casing is cemed as a circle.  This will be from the Dake an existing go producing for the control of the case of the control o	a wildcat well ta formation.  gas well, as in mation in the dill or deepen direction.	illed with mud and will be deepended to test the From Although this will dicated in Rule gas well.	s a circulatin ed to total de ntier formatio ell is located C-3, it will n	To be g medium pth of 5 n. Exis less th ot be dx present production	determined  After surface  650', using natural  sting production is  an 4960 feet from  cilled to the



#### ENGINEER'S AFFIDAVIT

STATE OF WYOMING County of Sweetwoter

I, R.C. Day, of Rock Springs Wyoming, hereby certify that this map was made from notes taken during an actual survey made under my direction by C.M. Koritnik on March 18th and 19th, 1964; and that it correctly represents the location thereon with section measurements based on the Township Plat of Section 22, T.3N., R.24E.

Electrical Engineer

Ditah Registration № 1295

#### LOCATION DATA

WELL-R.O. Murphy Nº 7

FIELD - Clay Basin

LOCATION

2210' From South Line 2099' From East Line NW NW SE Sec 22, T.3N., R24E

Daggett County, Utoh

ELEVATION

6622

By Stadio Levels from R.D Murphy Well Nº 6W

SURVEYED BY

CM. Koritnik March 18th and 19th, 1964

DATE OF REPORT

Morch 20 th 1964

REMARKS

Weather -18 th and 19th Windy, snow and Cold Well Elevation for Ground as Graded

2 1 40

REVISIONS			MOUNTAIN FU	FI SIIF	PIYCO		
DESCRIPTION	DATE	BY	ROCK SPRINGS WYO.				
	- I		WELL L	OCATION			
			R.D. MURPHY WELL Nº 7  NW NW SE SEC. 22, T. 3 N., R. 24 E.  DAGGETT COUNTY, UTAH				
	-		DRAWN 3-20-64 DGH				
	L			364775	1 = 1000		
		,	CHECKED RUM KAL	DRWG,	14 7CEA		
			APPROVED \$	NO.	M-/654		

#### April 9, 1964

Mountain Fuel Supply Company P. O. Box 1129 Rock Springs, Wyoming

> Re: Notice of Intention to Drill Well No. R. D. MURPHY #7, 2210' FSL & 2099' FEL, of Section 22, T. 3 N., E. 24 E., Daggett County Utah.

#### Gentlemen:

This Commission cannot approve the drilling of the above mentioned well due to the fact that it is off the normal spacing pattern provided for in Rule C-3, General Rules and Regulations and Rules of Practice and Procedure, Utah State Oil & Gas Conservation Commission.

We note that this well is located within a federaly approved unit agreement. If a copy of said unit agreement is filed with this office as provided for in Rule A-3, of the above rules and regulations, the approval of this Commission to drill said well will not be required.

Therefore, we suggest that an unexecuted copy of the Clay Basin Unit Agreement be filed with this office prior to spudding in.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT EXECUTIVE DIRECTOR

#### GBF: cnp

cc:

Don Russell, District Engineer U. S. Geological Survey - Salt Lake City, Utah

H. L. Coonts, Petroleum Engineer 011 & Gas Conservation Commission - Moab, Utah





#### Budget Bureau No. 42-R356.5. Approval expires 12-31-60

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

LAND OFFICE	
LEASE NUMBER	
UNIT Clay Basin	•••

#### LESSEE'S MONTHLY REPORT OF OPERATIONS

	State	Vt	sh		, Cou	nty Dag	gett	F	ield	C	lay Basi	n		
		The f	ollowin	ng is	a corr	ect report o	f opera	tions and	proa	luction	(including	drilling		
					P.	O. Box 989		C	ompan	y <b>MO</b> U	NTAIN FU	ĘL SUPI	PLY C	OMPANY
					SALT ]	Lake City, Ut	AH	S	gned		ップ・ ど	nee	ly	, 
	Phone	·····		i		328-8315			gent's	title D	IVISIONAI			
	SEC. AND		RANGE	WELL No.	DAYS PRODUCED	BARRELS OF OIL	GRAVITY	CU. FT. OF ( (In thousand	GAS GAS R	ALLONS OF GASOLINE ECOVERED	BARRELS OF WATER (If none, so state)	(If drilling cause; date gasolin	REMAR ; depth; and resu e conten	KS if shut down ilt of test for t of gas)
	1.	)	0											
	NV 22	3	24	7	6							Locat	:1on	
														i
									-					
				-										
-						·								مناه المناه

NOTE.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor.

Inform		U for 0.9. G.C. C.
orm 9–331 May 1963)	/041	T IN TRI TE* Form approved. Budget Bureau No. 42-R14
L L	EPARIMENT OF THE INTERIOR verse sid	de) 5. LEASE DESIGNATION AND SERIAL N
<u> </u>	GEOLOGICAL SURVEY	Selt Lake 045051-A
SUNDR	Y NOTICES AND REPORTS ON WELL	6. IF INDIAN, ALLOTTEE OR TRIBE NA
(Do not use this form Us	n for proposals to drill or to deepen or plug back to a differ se "APPLICATION FOR PERMIT—" for such proposals.)	rent reservoir.
		7. UNIT AGREEMENT NAME
OIL GAS WELL	OTHER	Clay Basin
NAME OF OPERATOR		8. FARM OR LEASE NAME
Mountain Fuel Su	pply Company	R. D. Murphy
ADDRESS OF OPERATOR		9. WELL NO.
	ock Springs, Wyoming 82901	
See also space 17 below.)	t location clearly and in accordance with any State requirem	
At surface		Clay Basin - Prontier
2210, PRT, 5033,	FEL, IN IN SE sec. 22	11. SEC., T., B., M., OR BLK, AND SURVEY OR AREA
		22-3N-24E., SLB&M
i. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH   13. STATE
	Ground 6622'	Daggett Utah
<del></del>		
•	Check Appropriate Box To Indicate Nature of No	otice, Report, or Other Data
NOTIC	CE OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING WATER	SHUT-OFF REPAIRING WELL
FRACTURE TREAT		THE TREATMENT ALTERING CASING
SHOOT OR ACIDIZE		ING OR ACIDIZING ABANDONMENT*
REPAIR WELL	CHANGE PLANS (Other	Spud in, surface casing XX
(Other)		NOTE: Report results of multiple completion on Well completion or Recompletion Report and Log form.)
LT&C casing, meas at 401.91' KBM.	a depth of 420', a surface string of uring 397.01' net, 403.43' gross, we The casing was comented with 203 se ment returned to surface. Pressure	as run into the well and landed soks regular cement. About
500 psi each for	15 minutes; pressure held good.	
Presently drilli	ng at a depth of $1450^{\circ}$ , using $7-5/8^{\circ}$	" b1t. /
		그는 생님은 사람들이 들면 그렇게 현화를 받는다.
I hereby certify that the SIGNED	foregoing is true and correct General Manag	
(This space for Federal o		Divisions DATE May 18.1964
, v_noo aoa a cactat o	r State office use)	
-	r State office use)	Divisions DATE May 18,1964
APPROVED BYCONDITIONS OF APPRO	TITLE	Divisions DATE May 18,1964  DATE

SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to despen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)  OLD ON THE CONTROL OF THE CONTROL OF THE CONTROL OF SUCH PROPOSALOR.  OLD ON THE CONTROL OF THE CONTROL O	SL 045051-A
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to despen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)  OLD ON THE CONTROL OF THE CONTROL OF THE CONTROL OF SUCH PROPOSALOR.  OLD ON THE CONTROL OF THE CONTROL O	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.    Comparison of Well   Comparison   C	. IF INDIAN, ALLOTTEE OR TRIBE
OIL WELL WELL STARD WITH SUPPLY COMPANY  AAMB OF OFBRATOR  **O. Box 1123, Rock Springs, Wyoning \$2901  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  LOCATION OF WELL (Report locatio	•
NAME OF OFBRATOR  AND OF OFBRATOR  O. BOX 1129, Rock Springs, Wyoming 82901  JOANNIO OF WELL (RAPORT location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  210' FSL, 2099' FEL, HW HW SE sec. 22  THENTY NO.  18. BLEVATIONS (Show whether DF, HT, GR, etc.)  KB 6634.90'; DF 6632.30'  Check Appropriate Box To Indicate Nature of Notice, Report, or Oth  NOTICE OF INTERTION TO:  WATER SHUT-OFF PRACTURE THEAT  SHOOT OR ACIDIZE  REPAIR WELL  (Other)  SUBSEQUENT  (Other)  Supplementate  (Other)	. UNIT AGREEMENT NAME
Domestain Fuel Supply Company  Address of Oferator  O. O. Box 1129, Rock Springs, Wyoning 82901  Location of Well. (Report location clearly and in accordance with any State requirements.*  Location of Well. (Report location clearly and in accordance with any State requirements.*  In surface  210' FEL, 2099' FEL, NN NN SE sec. 22  I I  PERMIT NO.  IS. ELEVATIONS (Show whether DF, RT, OR, etc.)  I KB 6634.90'; DF 6632.30'  Check Appropriate Box To Indicate Nature of Notice, Report, or Othen Notice of Internation to:  WATER SHUT-OFF  PEACTURE TREAT  SHOOT OR ACIDIZE  ARANDON*  CHANGE FLANS  CHANGE FLANS  CHANGE FLANS  COTHER WELL  (Other)  DESCRIBE MOVERS OR COMPLETES OFERSTRONS (Clearly state all pertinent details, and give portinent dates, in proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical dent to this work.)*  The Supplementary of the Supplem	lay Basin
ADDRESS OF OPERATOR  O. Box 1129, Rock Springs, Wyoming 82901  LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  210' FSL, 2099' FEL, NV EN SE SEC. 22  II. REVATIONS (Show whether DF, RT, OR, etc.)  LEGATH NO.  Check Appropriate Box To Indicate Nature of Notice, Report, or Other Notice of Invention 20:  WATER SHUT-OFF FRACTURE TREAT  MULTIPLE COMPLETE  ABANDON'  CHANGE PLANS  CHANGE PLANS  (Other)  DESCRIBE PROPOSED ON COMPLETED OPERATIONS (Clorely state all pertinent details, and give pertinent dates. Inc. proposed on the subject well is directionally defice, give subsurface locations and measured and true vertical 6 nent to this work.)*  Tender of Prontier formation.  Sample top of Frontier formation at 5474'	. FARM OR LEASE NAME
DOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  210° FBL, 2099° FEL, NW NW BE sec. 22  1. PERMIT NO.  1. REVARIONS (Show whether DF, RT, GR, etc.)  1. KB 6634.90°; DF 6632.30°  Check Appropriate Box To Indicate Nature of Notice, Report, or Other Notice of Invention to:  Subsequent  TEST WATER SHUT-OFF  FRACTURE TERAT  SHOOT OR ACIDIZE  ADANDON*  CHANGE FLANS  (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, incompetition or Recompletion of Recompletion or Recompletion or Recompletion or Recompletion of Recompletion or Recompletion o	R. D. Murphy
NOTICE OF INTERNATION TO:  TEST WATER SHUT-OFF FRACTURE TREATMENT SHOOT OR ACIDIZE REPART WILL COMPLETE ABANDON' CHANGE FLANS CHANGE FL	. WELL NO.
REALIZED PROCESSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, in entit of the work).  See also space 17 below.)  ARM 6634.90'; DF 6632.30'  Check Appropriate Box To Indicate Nature of Notice, Report, or Oth NOTICE OF INTENTION TO:  SUBSEQUENT WATER SHUT-OFF  FRACTURE TREAT  MULTIPLE COMPLETE  ABANDON'  CHANGE PLANS  (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, in entit of this work).*  The subject well is at a depth of 5476', tripping in hole with core ore Frontier formation. Sample top of Frontier formation at 5474'	O. FIELD AND POOL, OR WILDCAT
Check Appropriate Box To Indicate Nature of Notice, Report, or Oth  NOTICE OF INTENTION TO:  SUBSEQUENT  TEST WATER SHUT-OFF  FRACTURE TERAT  MULTIPLE COMPLETE  ABANDON*  (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give empletion or Recompletio nent to this work.)*  The subject well is at a depth of 5476', tripping in hole with core ore Frontier formation.  Sample top of Frontier formation at 5474'	av Resin - Prontier
Check Appropriate Box To Indicate Nature of Notice, Report, or Othe NOTICE OF INTENTION TO:  SUBSEQUENT TEST WATER SHUT-OFF PULL OR ALTER CASING PRACTURE TREAT MULTIPLE COMPLETE SHOOT OR ACIDIZE ABANDON*  (Other) Change Plans (Other) Supplementary (Note: Report results of Completion or Recompletion proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical denent to this work.)*  The subject well is at a depth of 5476', tripping in hole with core over Frontier formation. Sample top of Frontier formation at 5474'	1. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Check Appropriate Box To Indicate Nature of Notice, Report, or Othen Notice of Intention to:  Subsequent Test water shut-off Full or alter casing Mulciple Completed Test water shut-off Fracture Test water shut-off Substantial Shoot or acidize Abandon' (Other) Supplementary (Note: Report results of Completion or Recompletion or Recom	
Check Appropriate Box To Indicate Nature of Notice, Report, or Othen Notice of Intention to:  Subsequent Test water shut-off Full or alter casing Mulciple Completed Test water shut-off Fracture Test water shut-off Substantial Shoot or acidize Abandon' (Other) Supplementary (Note: Report results of Completion or Recompletion or Recom	2-38-24E., SLB&M
Check Appropriate Box To Indicate Nature of Notice, Report, or Oth  NOTICE OF INTENTION TO:  TEST WATER SHUT-OFF PULL OR ALTER CASING MULTIPLE COMPLETE SHOOT OR ACIDIZE REPAIR WELL (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, inc proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical density of the subject well is at a depth of 5476', tripping in hole with core over Frontier formation. Sample top of Frontier formation at 5474'	2. COUNTY OR PARISH 13. STATE
TEST WATER SHUT-OFF  FRACTURE TREAT SHOOT OR ACIDIZE REPARR WELL (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give entinent dates, ine nent to this work.)*  The subject well is at a depth of 5476', tripping in hole with core over Frontier formation.  Subsequent WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING ((Other))  CHANGE FLANS ((NOTE: Report results of Completion or Recompletion or	Daggett Uta
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent datas, ine proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical described by the subject well is at a depth of 5476', tripping in hole with core proposed work. Sample top of Frontier formation at 5474'.	er Data
SHOOT OR ACIDIZE REPAIR WELL (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, inc proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical drilled. Subject well is at a depth of 5476', tripping in hole with core ore Frontier formation. Sample top of Frontier formation at 5474'	r report of:
REPAIR WELL  (Other)  DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, ine proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical dries.  The subject well is at a depth of 5476', tripping in hole with core proposed.  Sample top of Frontier formation at 5474'	REPAIRING WELL
REPAIR WELL  (Other)  (Other)  (Other)  (Other)  (Note: Report results of Completion or Recompletion or Recomp	ALTERING CASING
(Other)  (Norm: Report results of Completion or Recompletion or Recompletion or Recompletion or Recompletion or Recompletion or Recompletion of Recompletion of Recompletion of Recompletion of Recompletion of Proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical direction this work.)*  The subject well is at a depth of 5476', tripping in hole with core one Prontier formation. Sample top of Frontier formation at 5474'	ABANDONMENT*
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, ine proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical denent to this work.)*  The subject well is at a depth of 5476', tripping in hole with core over Prontier formation. Sample top of Frontier formation at 5474'.	
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical denent to this work.)*  he subject well is at a depth of 5476', tripping in hole with core over Frontier formation. Sample top of Frontier formation at 5474'	on Report and Log form.)
	• Darrel to
$18^{\circ}$ . $18^{\circ}$	
I hereby certify that the foregoing is true and correct	
God Control Panager, Producing	
SIGNED 73.00. Cooff TITLE Pipeline Divisions	
(This space for Federal or State office use)	DATE 140 25, 1964







# Budget Bureau No. 42-R356.5

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

LAND OFFICE
Lease Number
UNIT Attack the same
UNIT Clay Basin

#### LESSEE'S MONTHLY REPORT OF OPERATIONS

State	Uta be f	ollowin	rg is	a com	nty <b>Dags</b> AY <sup>repor</sup> [9 <b>64</b>	t <b>t</b> opera	tions and p	lcle	Basin (including	drilling	and producing
				P.	O. Box 989		Com	pany MOU	NTAIN FU		LY COMPANY
***************************************				SALT 1	Lake City, Ut.	АH	Sign	ed	Tik	· n.e.	ly
Phone		· · · · · · · · · · · · · · · · · · ·			328-8315	· · · · · · · · · · · · · · · · · · ·	Age	nt's title [	IVISIONA		ACCOUNTANT
SEC. AND 1/4 OF 1/4	Twp.	RANGE	WELL No.	DAYS PRODUCED	BARRELS OF OIL	GRAVITY	Cu. Ft. OF GAS (In thousands)	GALLONS OF GASOLINE RECOVERED	BARRELS OF WATER (If none, so state)	(If drilling, cause; date a	EMARKS depth; if shut down and result of test for content of gas)
			2								
(	2		7	) ,	,						
i, nu 🥹	3. /	24	7	MICH						Omna A	3.3 e/99/ek
2 62		4.4		0			-			May	ded 5/17/64 31, 1964. /
İ										at 5	ing Casing 678'
										:	Ē
	į				В						
	i					ir -		-			
											·
										-	
	· .		أبد								

Note.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor.

Form 9-329 (January 1950)

Form 9-331 (May 1968)	CENTED STATES	SUBMIT IN TRIPLICATED	Form approved, Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SESIAL NO.
i	DEPARTM. OF THE II	NTERIOR verse side)	510 045051-A
			6. IF INDEAN, ALLOWTHE OR THE NAME
(Do not use this for	RY NOTICES AND REPORT for proposals to drill or to deepen	or plug back to a different reservoir.	
	Jee "APPLICATION FOR PERMIT-" f	or such proposais.)	7. UNIT AGREEMENT NAME
OIL GAS WELL D			Clay Basin
2. NAME OF OPERATOR	OTHER		8. FARM OR LEASE NAME
Mountain Fuel St	mply Company		R. D. Murphy
8. ADDRESS OF OPERATOR			9. WHLL NO.
P. O. Box 1129,	Rock Springs, Wyoming	32901	7
4. LOCATION OF WELL (Rep See also space 17 below. At surface	ort location clearly and in accordance	with any State requirements.*	10. FIRLD AND POOL, OR WILDCAT  Clay Resin - Frontier
2210' FSL, 2099'	FEL, NW NW SE 24-3N-2	+1 <u>E</u>	11. BEO, T. R., M., OR BLK. AND SURVEY OR AREA
			22-31-24E., SLBM
14. PERMIT NO.	15. RLEVATIONS (Show w	hether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
7	DF 6632.30';	KB 6634.901	Daggett Utah
16.	Check Appropriate Box To Ind	licate Nature of Notice, Report, or	Other Data
NO	CICE OF INTENTION TO:		UENT REPORT OF:
	[]		REPAIRING WELL
TEST WATER SHUT-OFF	PULL OR ALTER CASING MULTIPLE COMPLETE	WATER SHUT-OFF FRACTURE TREATMENT	ALTERING CAMING
FRACTURE TREAT SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDON MENT*
REPAIR WELL	CHANGE PLANS	(Other) Drlg, testi	ng, run sesing XX
(Other)	1_	Completion or Recomp	s of multime completion on Well pletion Report and Log form.)
DET 1: 5483'-5 DET 2: 5538'-5 moderate initial On final opening test. Recovered FOFP's 104-125 p DET 3: 5569'-59 Strong initial 1 On final opening test. Recovered FOFP's 209-104 p The Frontier for string of 5½" 00 5713,82' gross,	5570', Frontier, misrum 5570', Frontier, 10 ½ h 5570', Frontier, 10 ½ h 5570', Frontier, 10 ½ h 53, 15 minutes gauged 25, 350' gas cut mud. IHP 568', FSIP 2230 psi, FHP 568', Frontier, 10 ½ h 510w, gas up in 1½ minutes, 15 minutes gauged 11: 150' gas cut mud. IH 561, FSIP 1524 psi, FHP 5781 17#. K-80 and P-110.	our, ISI \(\frac{1}{2}\) hour, FO 1\(\frac{1}{2}\) hour, EV 1\(\frac{1}{2}\) hour, EV 1\(\frac{1}{2}\) hour, Such a steadily increasing 2854 psi, ISIP 2230 psi, 2812 psi.  The sur, ISI \(\frac{1}{2}\) hour, FO 105 minutes; 15 minutes 1274 Mcf, 00 Mef, decreasing to 677 P 2832 psi, ISIP 1960 psi, 2790 psi.  5476' to 5588'. At total 8 mand that IT&C casing, means and cemented with 235 seconds.	ors, PSI 1½ hours,  no minutes 236 Mcf,  to 321 Mcf at end of  IOFP's 104-104 psi,  nutes, FSI 1½ hours.  30 minutes 1123 Mcf.  Mcf per day at end of  IOFP's 251-188 psi,  depth, a production  asuring 5665,10' net,
18. I hereby certify that the SIGNED B. W	e foregoing is true and correct	General Manager, Product	ing 
(This space for Federa			
APPROVED BY CONDITIONS OF APP	ROVAL, IF ANY:	LE	PAR
CONDITIONS OF ALL			

		(
Form (May	9-331 1963)	

# THE INTERIOR (Other in verse side)

GEOLOGICAL SURVEY

Form approved. Budget Bureau No. 42-R1424 5. LEASE DESIGNATION AND SERIAL NO

	SLC	04	50 <b>51-A</b>		. <u>.</u>	
3	IP IND	LAN.	ALLOTTEE	OR	TREE	NAME

	TICES AND REPORTS ON WELLS  losals to drill or to deepen or plug back to a different reservoir.  CATION FOR PERMIT—" for such proposals.)	O. IF INDIAN, ADDITION OF TARREST
OIL GAS X OTHER		7. UNIT AGREEMENT NAME Clay Basin
2. NAME OF OPERATOR  Mountain Fuel Supply	Company	R. D. Murphy
B. address of operator P.O. Box 1129, Rock S	prings, Wyoming 82901	9. with #0.
<ol> <li>LOCATION OF WELL (Report location See also space 17 below.)</li> <li>At surface</li> </ol>	clearly and in accordance with any State requirements.*	Clay Basin - Frontier
2210' FSL, 2099' FEL,	NW NW SE 24-3N-24E	11. SEC., T., E., M., OR SLE. AND SURVEY OR ARTA 22-3N-24E., SEB&M
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	DF 6632.30'; KB 6634.90'	Daggett Iftah

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:
				WATER SHIPLOFF REPAIRING WELL
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WAIRE SHOTOE
FRACTURE TREAT		MULTIPLE COMPLETE	1_	FRACTURE TREATMENT ALTERING CASING
SHOOT OR ACIDIZE		ABANDON*	_	SHOOTING OR ACIDIZING ABANDONMENT
REPAIR WELL		CHANGE PLANS		(Other) Completion of well XX
(Other)				(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Pressure tested  $5\frac{1}{2}$ " OD casing and BOP's to 5500 psig each for 15 minutes; pressure test held good. Located top of cement behind casing at 5415' KBM.

Perforated the Frontier formation from 5533' to 5562' with 2 bullets and 2 jets per foot. Rigged up Halliburton and applied sandoil fracturing treatment. Broke down formation with 60 barrels drip oil mixed with 0.055ppg Adomite. Formation broke down at 3900 psig at 28 BPM. Applied treatment in one stage consisting of 30,000 gallons drip oil mixed with 22,500 pounds 20-40 mesh sand, 1650 pounds of Adomite, and 6 units RA material. Average pressure throughout job 3836 psig, average injection rate 25.8 BPM.

Flowed well back for a short 3 hours production test through the casing to clean up and gas flow stabilized at rate of 14,250 Mcf per day with a flowing wellhead pressure of 1200 psig. Shut well in and rigged up Otis snubbing equipment. Snubbed in a string of 2-3/8" OD, 4.7#, J-55, 8rnd thd EUE tubing, measuring 5512.48' net, 5541.35' gross, and landed tubing at 5523.88' KBM. Opened well through tubing on final production test and tested for 12 hours. At the end of the test period, the well was flowing gas at the rate of 4800 Mcf per day with a surface flowing tubing pressure of 1490 psig, casing pressure of 1580 psig, and separator pressure of 240 but to and the rig released on June 7. 1964. A 24-hour shut-in

					T)OIL WELL HOOK DEGLETING	
	period	resulted	in tubing pressur	of 1920 psig, casing pre	ssure of 1900 psig.	
18.	I hereby	certify that the	foregoing is true and correct	General Manager, P		
	SIGNED -	B. W.	foregoing is true and correct	TITLE and Pipeline Divis	ions pare June 8, 1964	-
	(This spa	ce for Federal	or State office use)			

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:



STATE OF UTAH
OIL & GAS CONSERVATION COMMISSION
310 NEWHOUSE BUILDING
SALT LAKE CITY 11, UTAH

#### REPORT OF WATER ENCOUNTERED DURING DRILLING

Well Name & Number:	R. P. Murph	x # 7	observation and the state of th
Operator Mountain	Fuel Supply Co, Add	ress 521+ Lake	Phone <u>378-8</u> 3/5
Contractor Lewmon 7	Drilling Assoc Inaga	ress Denver, Cal	2. Phone
Location: Nw \ SE \ Sec	. 22 T. 3 N R. 24 E	Daggett	Councy, Utah.
Water Cambra Y	nc, Valume	, J.J.	Quality
From 1	Co Flow Rate	or Head	Fresh or Salty
1			***************************************
2.			
3			
4		E AGRESANT CASE	· Jul
5. (Calibration 30)	i jato Longia Grego Motoria i carifeg		
Formation Tops:	Continued on rever	ee hay chaare ' eer, ee baara ee feele	
Remarks:	/	by Distor	B. Fras

MOTE: (a) Upon diminishing supply of forms, please inform the Commission

(b) Report on this form as provided for in Rule C-20, General Rules and Regulations and Rules of Practice and Procedure, (See back of form)

U

# UNITED STATES SUBMIT DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE

Form approved.
Budget Bureau No. 42

NO.

(See other in-		3.3
structions on reverse side)	5. LEASE DESIGNATION JAR	D SERIAL

			<u></u>		-AL 3		ú				SLC	0450	זיינכנ	9	<u>.</u>
,	WELL CO	MPLE	TION C	OR RECO	MPLE	TION I	REPORT	ANI	) LO	G *	6. 1F	INDIAN		TYPE OR THIS	MAK Q V
la,	YPE OF WEL	L:	OIL	GAS WELL	ΥX	DRY .	Other				7. UN	III for	EEMAN	r Name -	<del></del>
b, 1	TYPE OF COM	PLETION			-terus	DAT C.	Other	-			Cl	ay Be	asin	N. A. 3. 2. 2.	
	WELL XX	WORK OVER	DEEP-	PLUG BACK	Di ni	esvr.	Other	:			1	RM OR		NAME	
2. N	AME OF OPERAT	OR					<del></del>		t		R. :	D. M	urph	y i i i i i	- -
	Mountain	Fuel	Supply	Company			.图	7	i 		9. W	DLL NO.	,		-
8. A	DORRES OF OPER	ATOR	-								-	7			<del></del>
<del></del>	CATION OF PARK	-1220	. Rock	Springe	Wvon	ing.			: • <u> </u>		1			L, OR WILDCAT	
	<i>l</i> ocation"or" whi it surface	L <del>(Repo</del>	ri loverion i	crearry unwin	accorata	ice with an	y State requi	ement	•)•		1	· 11		or BLOCK AND	<u> </u>
	2210' FSI	, 209	9' FEL	, NW NW S	E sec	. 22					, o	R AREA			
4	t top prod. into	erval rep	orted below	7			₹		;		22-	311-5	4Ε.,	SLB&M	
Å	AS SDOVE t total depth						•				l : ,				
	As above	:			14.	PERMIT NO.		DATE 1	ssund			OUNTY.	OR .	13. STATE	
						<b>-</b>					1 _	gett		Utah	
15. D	ATE SPUDDED	16. DAT	TE T.D. BEAC	CHED 17. DAT		. (Ready t			ATIONS (I				19. 1	LLAV, CASINGH	EAD
	(15/64		0/64	6/7/			<del></del>		14.90		6632		-		· · · · · · · · · · · · · · · · · · ·
	TAL DEPTH, MD 4	A TVD		BACK T.D., MD &	TVD	22, IF MUL HOW M	TIPLE COMPL. ANY*	'	23. INT	ERVALS LLED BY	10-56	712 I	 γrα ∴ Ι	CANILE TO	) ) ) )
50	781 RODUCING INTER	WAY (@)	5636		n norma		AND TWD)	- 1		<del>-&gt;</del>	0-70	10	1 25	. WAS DERECT	TONAL
	33'-5562'					a, name (s	LD AND XID)				1. ;		.   -	SURVEY MAI	
	755 7702	, 110	MUICI.		•								2	Yes	
26, T	TPE ELECTRIC A	ND OTHE	R LOGS RUN		<del></del>			<del></del>	i		<del> </del>		27. W	AR WELL COR	MD
Ħ	L, sonic,	ML, C	RN Benk	oton							5 .	-	Ye	s	
28,	<u></u>	···		CAS	ING REC	CORD (Rep	ort all strings	set in	well)			7			
-	CASINO SIZE	WEIG	HT, LB./FT.				LE SIZE		CEA	ENTING	RECORD	3.3		AMOUNT PU	rind ,
	-5/8	40.		401.91			1/4"		sack		-			none	
5	-1/2	17.	.0	56781	КВМ	_	5/8"	235	sack	.s		<u> </u>		none	
4		_				_	·				· · · · ·				
29.	l <del></del>	<u> </u>	7 11	NER RECORD	<del></del>	_!	<del></del>		30.		TUBING	2 DECY	OP D	<del></del>	
ça.	SIZE	TOP (B		OTTOM (MD)	1	CDMENT*	SCREEN (MO		SIZE	T	DEPTH	<u> </u>	<del></del> -	PACKER SET	(MD)
				· · · · · · · · · · · · · · · · · · ·	-				2-3/8		55 <b>23</b> •			mone	•
											//-				<del>-</del>
	ERFORATION REC				- !!		82.	ÅCI	D, SHOT	, FRAC	TURE, C	EMEN	r squi	EEZE, ETC.	
2	NCF II ko	ne sh	nots and	d 2 15/38	2" bul	llets	DEPTH INT			AN	HOUNT 4	ND KIN	D OF M	ATERIAL USDI	)
p	er foot be	tweer	a 5533'	and 550	≤ '		5533'-5	5621						38,360	
	!						\ <u></u>							sand, 1	
										Adom	ite,	6 un	its	RA mater	181.
33.*					·	TO G G	OUCTION						<del></del>	<del> </del>	
	FIRST PRODUCTE	ON	PRODUCT	ION METHOD (	Flowing,			and ty	pe of pur	np)		WELL	STATU	(Producing	gr .
<b>C</b> 1	hut in		1									. ₽A#	t-in) Bhu	tin	<u>.</u>
	OF TEST	HOURS	TESTED	CHOKE SIZE		O'N. FOR	OIL-BBL.		GA8M	CF.	WAT	R-BBL		GAS-OIL RATIO	
6	/6-7/64	12		-	1108	PERIOD		* .	4800-	<b>-</b> 5450					· :
LOW.	TUBING PRESS.	CASING	PRESSURE	CALCULATED 24-HOUR BAT		-BBL.	GAS-	MCF.		WATER-	BBL.		OIL GI	AVITY-API (CO	RR.)
13	<b>60-</b> 1490	1575	<b>-</b> 1690				As a	bove	2		- : - <u>- : : : : : : : : : : : : : : : : : :</u>			* =	
34. D	ERPOSITION OF GA	s (Sold,	used for fu	el, vented, etc.	1						TEST	WITNES	SED BY		
V	ented.					<del></del>			·						<del></del>
	ST OF ATTACHM		4	ng n•±1	1	Cabzer	.hamaam : T	י. בית יחברו	n ar		#. <u>;</u>	13.5	:		÷
RA. T	Completion hereby certify	n repo	foregoing	II 1100.	rformati	on in comp	heren T	TD T	determin	ed from	all ava	nabis s	ecorde		
,			\(\)	utoutiled 1	v. ma ti	Ge	neral Me	inage	er, Pi	roduc	ing 8	ınd.			
_B	IGNED	W.	Ciofl		т		Pipeline				- 3 A	DATE	<u>Jun</u>	e 11, 19	164

#### COMPLETION REPORT

Operator:

Mountain Fuel Supply Company

Well:

R. D. Murphy No. 7

Area:

Clay Basin Unit

Location:

2210' FSL and 2099' FEL, Section 22, Township 3 North,

Range 24 East, Daggett County, Utah

Elevation:

6622' Ground, 6634.90' Kelly Bushing

Drilling Commenced:

May 15, 1964

Drilling Completed:

May 30, 1964 Testing Completed and Rig Released: June 7, 1964

Tops:

Mancos

Surface

Frontier

54541 55921

Total Depth:

Mowry 5678**'** 

Casing:

9-5/8" landed @ 401.91' KBM with 203 sacks

5-1/2" landed @ 5678' KBM with 235 sacks 2-3/8" landed @ 5523.88' KBM

Tubing:

Perforations:

5533' to 5562'

Producing Formation:

Frontier

Productivity:

4800 to 5450 Mcf with surface flowing tubing pressure

1360 to 1490 psig and casing pressure of 1575 to 1690 psig. This is following a sand fracture treatment.

SITP 1920 psig, SICP 1900 psig.

Remarks:

Cored from 5476' to 5615' with 122.5' recovered.

#### Drill Stem Tests

<u>No.</u>	Interval	Initial Flow	Initial Shut In	Final Flow	Final Shut In	Remarks
1	5483 <b>-</b> 5570	Misrun	The service of the se	en e		$\epsilon_{i} = i$
2	5538 <b>-</b> 5570	117-121 (30)	2218 (30)	123-130 (93)	2225 (90)	321 Mcf, 350; hgcm
3	5569-5588	268-218 (30)	1952 (30)	199-115 (105)	1533 (90)	677 Mcf, 150' hgcm

VB Gras:dgk

June 9, 1964



Field Clay Basin State Utah County Daggett Sec. 22 T	3N	R. 21E
Company Mountain Fuel Supply Company Farm R. D. Murphy Well No.	7	
Location 2210' FSL; 2099' FEL 6622' GR, 6634.		3
Drilling Commenced May 15, 1964 Completed May 30, 1		
Drilling Commenced May 15, 1964 Completed May 30, 1		-
Rig Released June 7, 1964 Total Depth 5678'  Casing Record 9 5/8" landed @ 401.91' KBM with 203 sacks	<del></del>	····
		<del></del>
5 1/2" landed @ 5678' KBM with 235 sacks		
Tubing Record 2 3/8" landed @ 5523.88' KBM	<del></del>	
Perforations 5533' to 5562'		
4800 to 5450 Mcf with surface flowing tubing pressure 1360 to 1490 I.P. Gas casing pressure of 1575 to 1690 psig. Oil	psig	and
SandsFrontier		
Shut-in Surface Pressures SITP 1920 psig, SICP 1900 psig	. , , .	
Remarks Cored from 5476! to 5615' with 122.5' recovered.		
Remarks		
	·····	
Formation Record		
MANCOS AT SURFACE	From	To
No samples. Shale, medium to dark gray, firm, silty to sandy; with occasional thin streaks	0 420	420 480
of sandstone, gray, fine-grained, tight. Shale, as above, micaceous; with occasional thin beds of sandstone, white	480	690
to light gray, firm, very fine-grained, tight, silty, calcareous. Shale, as above, very sandy.		·
Siltstone, medium gray, firm, sandy in part; with occasional thin beds of	690 750 -	750 810
shale, as above. Sandstone, light gray to medium gray, very fine-grained, firm, tight, carbo- naceous, argillaceous; interbedded with siltstone, as above, no show.	810	900
Sandstone, as above. Siltstone, medium to light gray, firm, sandy, carbonaceous, calcareous.	900	930
Siltstone, as above; interbedded with sandstone, white to light gray, very	930 1140	1140 1290
fine- to fine-grained, sub-angular, salt and pepper, occasional green grain, firm, friable, argillaceous, calcareous, no show.		
Siltstone, as above; with occasional thin beds of shale, as above. Siltstone, as above; interbedded with sandstone, white, medium- to coarse-	1290 1350	1350 1380
grained, sub-angular, fairly well sorted, firm, friable, slightly calcareous, abundant black and green grains, few orange, trace of yellow fluorescence,	1))0	1,000
_no cut; looks like mineral fluorescence.		
Siltstone, as above; trace of sandstone, as above. Siltstone, as above; with occasional thin beds of sandstone, light to medium	1380	1410 1620
gray, very fine-grained, tight, firm, very argillaceous; trace of light- brown to tan, siltstone, firm, slightly calcareous.		
Siltstone, as above; sandstone, as above, occasional large grain of clear and red chert; some bentonite.	1620	1920
Shale, medium to dark gray, firm, very silty to sandy, calcareous; inter- bedded with sandstone, medium to dark gray, firm, friable, very fine-grained.	1920	1980
sub-angular, tight, argillaceous, calcareous, salt and pepper, no shows; trace of siltstone, as above; with occasional thin bed of bentonite, white.		
Ditto; sandstone with trace of glauconite.		
Shale, medium to dark gray, firm, silty to sandy, intempodded with and the	1980	2160
Shale, medium to dark gray, firm, silty to sandy; interbedded with sandstone, medium to dark gray, very fine- to fine-grained, sub-angular, tight, firm, friable, salt and pepper in part, carbonaceous, calcareous; with occasional	1980 2160	2160 2490

C

Farm R. D. Murphy Company

Mountain Fuel Supply Company

	FORMATION RECORD FORMATION RECORD		
	From	To	ľo
	Shale, medium to dark gray, firm, very silty to sandy, carbonaceous; with occasional thin beds of sandstone, white to light gray, very fine- to fine-grained, sub-angular, fairly well sorted, firm, friable, tight, salt and pepper, calcareous, argillaceous, no show.	21,90	
	Ditto; sandstone, becoming more carbonaceous in part.  Shale, as above; interbedded with sandstone, as above.  Ditto; with occasional thin beds of siltstone, medium gray, firm, sandy, calcareous, with abundant grains of a tan color.	2540 2550 2600	2550 2600 2630
	Shale, medium to dark gray, firm, calcareous, silty; with occasional thin beds of sandstone, as above.	2630	2670
	Shale, medium to dark gray, firm, silty; with abundant tan grains or fragments?; with occasional thin beds of sandstone. as above.	2670	2700
	Shale, as above; with occasional thin beds of siltstone, as above.  Shale, as above: interbedded with sandstone, as above, with consideral	2700 2740	2740 2850
	Shale, as above; interbedded with sandstone, as above; with occasional thin beds of siltstone.  Shale, medium to dark gray, firm to soft, silty, calcareous; interbedded	2850	2990
	with sandstone, light to medium gray, very fine-grained, argillaceous, firm, friable, tight, salt and pepper in part.  Shale, as above.	2990	3370
	Shale, medium to dark gray, firm, silty, carbonaceous, calcareous, speckled in part, tan specks; with occasional thin beds of sandstone, very fine-grained, dark gray, firm, argillaceous, tight.	3370 3590	3590 3760
 	Shale, medium to dark gray, firm, silty, calcareous, some disseminated carbonaceous material; trace of sandstone, as above; few Inoceramus prisms.	3760	4120
	Shale, as above; interbedded with siltstone, medium to dark gray, firm to hard, sandy in part; few Inoceramus fragments.		4230
	Shale, medium to dark gray, firm, silty, carbonaceous, calcareous, occasional carbonaceous streak; with occasional thin beds of sandstone, light gray, very fine-grained, firm, tight, argillaceous, calcareous, salt and pepper in part, no show.	4230	4430
	Challe and the same		4490 4520
	Shale, as above, platy; Inoceramus fragment; with occasional thin laminae of sandstone, as above.	4520	4800
	Shale, medium to dark gray, firm, silty, calcareous, sandy in part, Inoceramus fragment; with occasional thin laminae of sandstone, light gray to medium gray, very fine-grained, salt and pepper, firm, friable, tight, very argillaceous in part, calcareous, no show.	4800	4950
	Shale, as above; with occasional thin laminae of sandstone, as above. Shale, as above; with occasional thin laminae of sandstone, as above.	5100 5320	5100 5320 5350 5370
	Shale, as above; with occasional thin beds of siltstone, light gray, firm; trace of pyrite.	5370	5454
	FRONTIER 5454. Same as above.		
	Shale, as above. Sandstone, white to light gray, fine-grained, sub-angular, fairly well	5460	5460 5474 5476
	sorted, hard, friable, looks tight, few black grains, calcareous, no show.		5536
	4' Shale, dark gray to black, firm, silty, carbonaceous. 1' Shale, as above, with coal partings.		
	9' Sandstone, light gray, very fine-grained, sub-angualr, hard, friable, tight, slightly calcareous, very carbonaceous, with abundant carbonaceous streaks and partings.		
	2' Shale, as above. 3' Sandstone, as above.		
	3' Sandstone, as above; interbedded with shale, as above.		

22

Well No.

Company

R. D. Murphy Mountain Fuel Supply Company

FORMATION RECORD

FORMATION RECORD

From

To

5536 5570

5570 5588

l' Coal, black.

7' Shale, as above.

3' Sandstone, as above; with abundant thin laminae of shale, as above.

5' Siltstone, medium gray, very hard, slightly calcareous, carbonaceous, has sugary texture.

4' Sandstone, as above; interbedded with shale, as above; with minor amounts of brecciation and minute faulting.

12' Shale, medium to dark gray, firm, hard, slightly calcareous.

Core #2

Cut 34', recovered 31.5'.

31.5' Sandstone, light gray to buff, fine- to medium-grained, sub-angular, fairly well sorted, looks porous, firm, friable, slightly calcareous, salt and pepper in part, glauconitic in part, cross-bedding in part, shaly in part, abundant fluorescence, yellow, some cut; core smells gases.

Core #3

Cut 18', recovered 18'.

2' Sandstone, light gray, fine-grained, sub-angular, fairly well sorted, firm, friable, looks tight, slightly calcareous, salt and pepper, some pinpoint fluorescence, yellow; with thin shale partings, medium to

dark gray, firm, silty.

8' Sandstone, light gray to buff, fine-grained, sub-angular, fairly well sorted, firm, friable, porous, slightly calcareous, salt and pepper,

with abundant carbonaceous streaks, good yellow fluorescence.

4' Sandstone, as above; with shale partings. 2! Sandstone, as above: interbedded with shale, as above, abundant open fracture, vertical in part.

2' Shale, as above.

MOWRY 55921

Core #4

Cut 27', recovered 13'. 13' Shale, medium to dark gray to black, hard, siliceous, micaceous,

occasional glob of secondary minerals, green.

Shale, dark gray to black, hard, siliceous, micaceous.

5686

5615

5588 5615

SLM 5678.18 Driller 5686 Schlumberger 5679

June 15, 1964

Mountain Fuel Supply Company P. O. Box 1129 Rock Springs, Wyoming

Attention: Mr. B. W. Croft, General Manager, Producing & Pipeline Div.

Re: Well No. R. D. Murphy #7
Sec. 22, T. 3 N., R. 24 E.,
Daggett County, Utah

#### Gentlemen:

Thank you for your 'Well Completion or Recompletion Report and Log" and Induction-Electrical Log. Upon reviewing these logs, it was noted that you also ran Sonic, Micro and Gamma-Ray Neutron Cemoton logs on the above mentioned well. It would be appreciated if we could receive copies of said logs.

It will also be appreciated if you would complete and return the enclosed Form OGCC-8-X, "Report of Water Encountered During Drilling".

Thank you for your consideration in these requests.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

KATHY G. WARNER RECORDS CLERK

kgw

Enclosure - Forms



C. R. HENDERSON

M. V. HATCH
C. S. THOMSON
B. H. CROFT
C. P. DLSON

EXECUTIVE DIRECTOR
C. B. FEIGHT



THE STATE OF UTAH

PAUL W. BURCHELL
CHIEF ENGINEER
BALT LAKE CITY
HARVEY L. COONTS
BOX 266
MOAB, UTAH

PETROLEUM ENGINEERS

#### OIL & GAS CONSERVATION COMMISSION

310 NEWHOUSE BUILDING 10 EXCHANGE PLACE SALT LAKE CITY 84111

June 15, 1964

Mountain Fuel Supply Company P. O. Box 1129
Rock Springs, Wyoming

Attention: Mr. B. W. Croft, General Manager, Producing & Pipeline Div.

Re: Well No. R. D. Murphy #7
Sec. 22, T. 3 N., R. 24 E.,
Daggett County, Utah

Gentlemen:

Thank you for your "Well Completion or Recompletion Report and Log" and Induction-Electrical Log. Upon reviewing these logs, it was noted that you also ran Sonic, Micro and Gamma-Ray Neutron Cemoton logs on the above mentioned well. It would be appreciated if we could receive copies of said logs.

It will also be appreciated if you would complete and return the enclosed Form OGCC-8-X, "Report of Water Encountered During Drilling".

Thank you for your consideration in these requests.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

KATHY G/WARNER RECORDS CLERK

kgw

Enclosure - Forms

Enclosed 6

Gray hle

UNITED STATES

LESSEE'S MONTHLY REPORT OF OPERATIONS

May me



Budget Bureau No. 42-R356.5. Approval expires 12-31-60

#### LAND OFFICE

LEASE NUMBER
UNIT Clay Basin

## DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

State	J.cah.			Cou	nty Dagget	t	Field	C).a	y Basin		***************************************	
wells)	for th	e mon	th of	<b>J</b> P.	UL 1964 O. Box 989	ļ,	tions and p 19, Com	banv MOL	JNTAIN FU	JEK SUPI	PLY COMPA	NY
				Salt 1	Lake City, Ut	AH 	Signe	ed	97,7	· nc	clij	
Phone					328-8315		Agen	ıt's title I	DIVISIONAL	L CHIEF	ACCOUNTA	NT
SEC. AND 1/4 OF 1/4	TWP.	RANGE	WELL No.	DAYS PRODUCED	BARRELS OF OIL	GRAVITY	Cu. Ft. OF GAS (In thousands)	GALLONS OF GASOLINE RECOVERED	WATER (If	(If drilling cause; date	REMARKS , depth; if shut do and result of test e content of gas)	own for
, NW 22	3	2年 (	7)	RI	o mugh					Comple		
, se 21	3	24	8							Comple		4
÷			·							÷		
						 				in		

runs or sales of gasoline during the month. (Write "no" where applicable.)

NOTE.—Report on this form is required for each calendar month, regardless of the status of operations, and must be filed in duplicate with the supervisor by the 6th of the succeeding month, unless otherwise directed by the supervisor.

NOTE.—There were runs or sales of oil; M cu. ft. of gas sold;



Budget Bureau No. 42-R356

LAND OFFICE
LEASE NUMBER
UNITClay Besin

#### UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

#### LESSEE'S MONTHLY REPORT OF OPERATIONS

State	•••••	Utah	•••••	Сои	ntyDag	gett	Field	l <b>C1</b>	ay Basin	
	The	followi	ng is	a corr	ect report o	f opera	tions and p	production	(including	drilling and producing
	-		•							THE CLIDDLY COMPANY
Agent's				P.	LAKE CITY IIT	68 AU 841	.11 Sign	pany MOU	OZ Z	JEL SUPPLY COMPANY
Phone				ORGI :	328-8315	M1 0 12	Ages	ea nt's title	DIVISIONAL	CHIEF ACCOUNTANT
SEC. AN	D Two	P. RANGI	W/	T	BARRELS OF OIL	T	Cv. Em. on Can	T	BARRELS OF WATER (If	REMARKS (If drilling, depth; if shut down
NW E 22	3	24	3	7.77	y Ay					Spudded 5/17/64 Completed as a Gas well 6/1/64 Depth 5678' Shut In.
SE W 21	3	24	8		·					Spudded 6/13/64 Completed as a Gas well 7/19/64 Depth 5436' Shut In

xrm C	• 93	45					<b>TR</b>		\$ \$   0	N AND	PROD	UCTIO	N	7	COMPA ROC	ANY K SPRINGS TION RE	, WYOMIN	• 3	N2	YE	22
OCAT	ION:	C	\A\	7	3 <sub>R</sub>	112	1		_	*	7			T	CO	unty GETT	7	TAH		10-22	
TATIO	N O	R CUS		•			240	***	*	12		Bill d	Ŵy.					TIME OF TES	T AM	10:	30
RIFIC		Terre	1	oxpo	KE		SERI T-6	AL NO		2	TYPE			HART I		STATIC D.		AD:	_ 7 1	CLOCK	ROT.
AETER			T	INCI		1		UNDS	1	OMTA	S. PRE	SS.		IS AT		T ON CHAR	T?		TYPE OF C	HART USER	· · ·
A1101				DEAD	WEIGH	T CH	ECK	STA	TIC F	OUND		TIC L	<u> </u>	Yes	oiff.	Diff	No.	Temp.	Root	<del></del>	riear Time
AETER EADIN			D.	W. Pre	:ss	431	.6	6	.65	5	6.	65	-	Fo	bund	Lef		Found	Left		Lag
				tic Pe						4 (1) 2	ica			L	<b>チ</b>	Ø		42°	42	6	hrs
	48 N				DIFFI	RENTI	AL TEST		e Militar		48°						S1	ATIC TEST			
n serie. Heritari	UP		FOUNI	000	NN	$-\Gamma$		UP	AS L		OWN		-	AS FC			S LEFT V. Meter	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	SQ. RT. V	ALUE, AS LI	FT
lan.	1	Meler		on.	Mete	<u> </u>	Man.	T	) ter	Man.	T	Aeter	#=		araj s			₹ √		x 100	
0	levi	0		10	80	-#	0	10	i e e	80	+-	30			14 V	Taker	1,99.	7		Rp	
0	十	10	-	50	60		10	10		60	+-	0						-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\	42.6 >	(100_	6.65
50	+-	9.7		.0	40	,	30	3		40		10					THE	RMOMETER			
50	14	9.7		20	20		50	5	0	20	2	20	M	AKE —	fox	boro					
70	6	9.6		0	0		70	7	9	0	,	0	_	30 <b>ʻ</b>	ſ	ANGE +/50	de la la	FI	87/6	AL NO.	
90	8	9, 8		\$ -3. \$ 7.			90	90	)			rifina Mil	-	U	AS	FOUND	OWN	100	UP A	S LEFT DO	)WN
¥• 1277	Çă.		17 K				Ay.		. 6		3		11	est erm	Rec. Therm	Test Therm	Rec. Thern	Test Therm	Rec. Therm	Test Therm	Rec. Therm
		Ý4.					i Prižes				i Ja						A NOW	Negar			
W.		V.										i Nga			1949-b 1017-75					. Sprace	i in
	(\$;5)er -6-	Size		<b>3</b> "	OR · /	IFICE F						-			N 444	ieL	RIFICE FIT	TING OR UN	JUNION	* 10 to	
ges S					· /,	300	i Piraki	maged	Orifice	Condi	ion Dirty	: tiv   <b>?</b>				erial No. 🖋	900		• Size	3.00	9 8 10
icro H					i Ywn i A		Micro V	ertical		· W		- A	M	eter Tu	be	Upstream Downstream	ID S	<u> </u>			
			Ma			TE	ĹEM	ETER	RING	i Ngay.						GRAVIT			ATMOS.	garage selection	
Milita T			FFE	RENT		- 1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (		· v		UND	PRE	SSUF		FT		REMARI	KS:	FF PE	V AR	20	
UP		DO	WN	U	P	FT DO	WN	U			WN		iP	DC	NWN	7/45		ff <i>PEI</i> Beari			
1.00				TEST	TRANS				TRANS			<b> </b>	TRANS	1	TRANS	Kepa	KK_	Deari	ng	965 <u>(19</u> 57) 2 <b>6</b> 63(20)	e tre i di. Militare
<b>%</b>	Į,	100%		0%		100%	<b>-</b>	0%		100%		0%	-	100%	-					的是自己的 Application	
%		75 %		25%		75%		25%	AG	75%	2.5	25%		75%							
		50%	ett i	75%		25%	<u> </u>	50%		25%		75%	1.44	309	•	M.F.S.		) kng	1.7	16.	<u> </u>
96		25%		100%		0%		75%		0%		100%		0%		TESTE	of Aug and	knig_	WOX	nera	i i kana da ka
%		0%		1007	1	770	120	, T		77		1.557		"		WITNE	S <b>S</b> :		<b>以外来的</b> 图	green and	er British & Lon

7

hare 626

ž gev



180 EAST FIRST SOUTH . P. O. BOX 11368 . SALT LAKE CITY, UTAH 84139 . PHONE (801) 534-5555

April 10, 1984

Working Interest Owners
Clay Basin Unit
Daggett County, Utah and
Sweetwater County, Wyoming

#### Gentlemen:

Mountain Fuel Supply Company, as designated operator of the Clay Basin Unit, hereby resigns as Unit Operator under the provisions of Section 4 of the Unit Agreement subject to: WEXPRO Company being designated successor Unit Operator by the committed working interest owners and approval by the Bureau of Land Management.

WEXPRO Company, a wholly owned second tier subsidiary company of Mountain Fuel Supply Company, has assumed all of the development and producing operations of Mountain Fuel. Office and operating personnel have been transferred to WEXPRO so there will be no physical change in operations.


MOUNTAIN FUEL SUPPLY COMPANY

BY:

W. F. Edwards Vice President

cc: Mr. E. W. Guynn
Chief, Branch of Fluid Minerals
Bureau of Land Management
136 East South Temple
University Club Building, 11th Floor
Salt Lake City, UT 84111

# CLAY BASIN UNIT Daggett County, Utah



24E

UNIT OUTLINE (UTU63009X)

FRONTIER PA

11,162.43 ACRES

FRONTIER PA ALLOCATION FEDERAL 82.17194% STATE 9.63096% FEE 8.19710% 4,765.64 Acres



#### United States Department of the Interior

BUREAU OF LAND MANAGEMENT UTAH STATE OFFICE 136 E. SOUTH TEMPLE SALT LAKE CITY, UTAH 84111

April 26, 1984

WEXPRO Company P.O. Box 11368 Salt Lake City, Utah 84139

> Re: Successor Unit Operator Clay Basin Unit Daggett County, Utah and Sweetwater County, Wyoming

#### Gentlemen:

On April 26, 1984, we received an indenture dated April 10, 1984, whereby Mountain Fuel Supply Company resigned as Unit Operator and WEXPRO Company is accepted as Successor of Unit Operator for the Clay Basin Unit Agreement, Daggett County, Utah and Sweetwater County, Wyoming.

The indenture was executed by both parties. The signatory parties have complied with Section 6 of the unit agreement. The instrument is hereby accepted effective as of April 26, 1984. Please advise all interested parties of the change in unit operator.

Sincerely,

E. W. Guynn

Chief, Branch of Fluid Minerals

Enclosure



WEXPRO COMPANY LANDS & LEASING

Chapley 14 June 88 Clay Basen Unit #13 Sec 23, 3N, 24E access tank w/ frewall O well head. lmergen aj fit dehy at shed.

(12/93)

Page 1 of 5

#### MONTHLY OIL AND GAS PRODUCTION REPORT

OPERATOR NAME AND ADDRESS:		<del></del>	UTAH ACCOUNT NUMBER: N1070					
JOHN JOOSTEN WEXPRO COMPANY PO BOX 11070 SALT LAKE CITY UT 8414	÷7		REPORT PERIOD (MONTH/YEAR): 9 / 96  AMENDED REPORT (Highlight Changes)					
Well Name	Producing	Well	Days	T	Production Volumes			
API Number Entity Location	Zone	Status	Oper	OIL(BBL)	GAS(MCF)	WATER(BBL)		
BUG #4 · 4303730542 00995 36S 26E 16	DSCR					WITTERCORD		
BUG 17 4303730793 00995 36S 26E 16	DSCR							
BUG #10 4303730591 01010 36S 26E 22 BUG 14	DSCR							
4303730605 01020 36S 26E 17 BUG #15	DSCR							
4303730606 01020 36S 26E 17 BUG 16	DSCR							
73730607 01020 36S 26E 17	ISMY							
4303730610 01020 36S 26E 17	DSCR		, , , , , , , , , , , , , , , , , , ,					
4300915625 01025 03N 24E 22 CLAY BASIN UNIT 7	FRTR							
4300915631 01025 03N 24E 21 CLAY BASIN UNIT 8	FRTR							
4300915632 01025 03N 24E 19 CLAY BASIN UNIT #9	FRTR					<del></del>		
4300915633 01025 03N 24E 15 CLAY BASIN UNIT 12	FRTR							
4300915636 01025 03N 24E 22 CLAY BASIN UNIT 13	FRTR							
4300915637 01025 03N 24E 21	FRTR							
		•	TOTALS					
					<b>V</b>			
OMMENTS:								
······································	<del></del>	·						
·		·				·		
nereby certify that this report is true and complete to the	he best of my	knowledge.		Da	te:			
me and Signature:								
and Signature.				1	elephone Number:			

Division	nf	Oil.	Gas	and	Mining

#### OPERATOR CHANGE WORKSHEET

Attach all documentation received by the division regarding this change. Initial each listed item when completed. Write N/A if item is not applicable.

Routing	· · · · · · · · · · · · · · · · · · ·
1-LEC	6-I)EC
2 <del>-GLH</del>	7-KDR /
3-DTS ·	8-SJ
4-VLD	9-FILE
S-R-IF-	

				3-KJF					
		nange of Operator (well sold)    esignation of Operator    Operator	gnation of Agent rator Name Change Onl	y					
The	op	erator of the well(s) listed below has change	d, effective: <u>4-26-84</u>	· · · · · · · · · · · · · · · · · · ·					
TO:	(ne	ew operator) <u>wexpro company</u>	FROM: (old operato	or) MOUNTAIN FUEL SUPPLY CO					
	(11)	(address) PO BOX 11070	_ rkow: (old operate _ (address						
		SALT LAKE CITY UT 84147	_ (address	SALT LAKE CITY UT 84139					
			-						
		Phone: _(801)530-2586	_	Phone: <u>(801)534-5267</u>					
		Account no. N1070	-	Account no. N0680					
		ricodulit no.	•	Account no					
WEI	LL(	S) attach additional page if needed:	*CLAY BASIN UNIT						
Name	e: :	**SEE ATTACHED** API:	Entity: S	T R Lease:					
Name		API:	Entity: S	T R Lease:					
Name		API:	Entity: S	T R Lease:					
Name	_	API:	Entity: S	T R Lease:					
Name	_	API:	Entity: S	T R Lease:					
Name	_	API:	Entity: S	T R Lease:					
Name	:: 	API:	Entity: S	T R Lease:					
	1. (r649-8-10) Sundry or other legal documentation has been received from the FORMER operator (attach to this form). **See Comments*.  2. (r649-8-10) Sundry or other legal documentation has been received from the NEW operator (Attach to this form). **See Comments*.  3. The Department of Commerce has been contacted if the new operator above is not currently operating any wells in Utah. Is the company registered with the state? (yes/no) If yes, show company file number:  4. FOR INDIAN AND FEDERAL WELLS ONLY. The BLM has been contacted regarding this change. Make note of BLM status in comments section of this form. BLM approval of Federal and Indian well								
NA	5.	Changes have been entered in the Oil and G	as Information System	(3270) for each well listed above.					
NA	6.	Cardex file has been updated for each well	listed above. * Su Com	ments					
Lic		Well file labels have been updated for each							
<u>N/A</u>	8.	Changes have been included on the monthl distribution to Trust Lands, Sovereign Lands	y "Operator, Address, a	and Account Changes" memo for					
<u>fic</u>	9.	A folder has been set up for the Operator Confor reference during routing and processing	hange file, and a copy o of the original documer	f this page has been placed there nts.					

Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. LEASE DESIGNATION AND SERIAL NO.

SEE ATTACHED SHEET

SUNDRY NOTICES AND REPORTS ON WELLS 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT -" for such proposals 7. IF UNIT OR CA, AGREEMENT DESIGNATION SUBMIT IN TRIPLICATE **CLAY BASIN** 1. TYPE OF WELL UNIT AGREEMENT # 892000323B OΙΙ GAS 8. WELL NAME AND NO. WELL X WELL OTHER 2. NAME OF OPERATOR SEE ATTACHED SHEET WEXPRO COMPANY 9 APIWELL NO 3. ADDRESS AND TELEPHONE NO. SEE ATTACHED SHEET P. O. BOX 458, ROCK SPRINGS, WY 82902 (307) 382-9791 10. FIELD AND POOL, OR EXPLORATORY AREA 4. LOCATION OF WELL (FOOTAGE, SEC., T., R., M., OR SURVEY DESCRIPTION) CLAY BASIN 11. COUNTY OR PARISH, STATE SEE ATTACHED SHEET DAGGET COUNTY UTAH CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF N ER DATA TYPE OF SUBMISSION Notice of Intent Abandonment Change in Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection VARIANCE Dispose Water

Wexpro Company is requesting a variance from the requirement to install Enardo vent stack valves on the storage tanks for the wells listed on the attached sheet. This request is due to the potential freezing problems encountered with the Enardo vent stack valves. In the past storage tanks have been over pressured, as they could not vent, and once over pressured ruptured causing the top of the tank to be thrown from the tank. The potential tank damage, loss of fluids, fire and ground contamination are our primary safety and environmental concerns for this request.

RECEIVED

OCT 2 8 2002

DIVISION OF OIL, GAS AND MINING

Accepted by the Utah Division

Date:

Bv:

Sixt of well

10-29-02 LBO

Federal Approval Of This

Action Is Necessary

Title G. T. Nimmo, Operations Manager Date October 21, 2002

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title 18 U.S. C. Section 1001, makes it a crime for any person knowingly and wiltfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

<sup>(</sup>Note: Report results of multiple completion on Well Completion or Kecompetion or Kecompetion or Kecompetion Report and Log rorm.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WELL NAME	API NUMBER	LEGAL DESCRIPTION	COUNTY, STATE	UNIT CA PA NUMBER	LEASE NUMBER
CLAY BASIN FIEL	D UNIT			892000323B	
UNIT NO. 1	4300915625	SW NW 22-3N-24E	DAGGETT, UT		SL-045051 <b>-</b> a
UNIT NO. 7	4300915631	SE SW 21-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 8	4300915632	NE NE 19-3N-24E	DAGGETT, UT		SL-062508
UNIT NO. 9	4300915633	NE SW 15-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 12	4300915636	NW SE 22-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 13	4300915637	SE NW 21-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 14	4300915638	NW SW 20-3N-24E	DAGGETT, UT		SL-062508
UNIT NO. 15	4300915639	SE SW 23-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 16	4300930003	SW NW 25-3N-24E	DAGGETT, UT		SL-045049
UNIT NO. 17	4300930004	NW NE 27-3N-24E	DAGGETT, UT		SL-045053-a
UNIT NO. 18	4300930006	NW NW 23-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 19	4300930008	SE SE 17-3N-24E	DAGGETT, UT		SL-045051 <b>-</b> b
UNIT NO. 20	4300930007	NW NW 22-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 22	4300930001	NW SE 16-3N-24E	DAGGETT, UT		ML-807
UNIT NO. 23	4300930009	SE NW 26-3N-24E	DAGGETT, UT		SL-045053-b
UNIT NO. 61	4300930060	NE SE 20-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 62	4300930061	SE SE 21-3N-24E	DAGGETT, UT		SL-045051-b

#### Form 3160- 5 (August, 2007)

#### UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

	5. Lease Serial No.							
SUNDRY NOTICES AND RI	6. If Indian, Allott	SL-045051-a						
Do not use this form for proposal abandoned well. Use Form 3160-3	s to arill or to re-( (APD) for such pi	enter an roposals.	6. If Indian, Allou	N/A	2			
SUBMIT IN TRIPLICATE - Other Instru			7. If Unit or CA.	Agreement Name	and/or No.			
1. Type of Well	ctions on page 2		Clay Basin	Unit				
Oil Well Gas Well Other			8. Well Name and		10			
2. Name of Operator			Clay Basin 9. API Well No.	Unit	12			
Wexpro Company	21 Phone No Gual	luda araa aada)	9. API Well No.					
	3a. Address 3b. Phone No. (include area code)							
P.O. Box 458 Rock Springs, WY 82902	307.3	82.9791	10. Field and Poo	l, or Exploratory	Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Lat.	40.9814		Frontier				
2210' FSL 2099' FEL NW SE 22-3N-24E	Long.	-109.19028	11. County or Par Dagge		Utah			
12. CHECK APPROPRIATE BOX(S) TO INDICA	TE NATURE OF	NOTICE, REPOR						
TYPE OF SUBMISSION		YPE OF ACTION						
Notice of Intent Acidize	Deepen	Production ( S	Start/ Resume)	Water Shut	t-off			
Altering Casing	Fracture Treat	Reclamation		Well Integr	rity			
Subsequent Report Casing Repair	New Construction	Recomplete		Other _				
Change Plans	Plug and abandon	Temporarily A	Abandon					
Final Abandonment Notice Convert to Injection	Water Dispos							
13. Describe Proposed or Completed Operation (clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will performed or provide the Bond No. on file with the BLM/ BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has determined that the site is ready for final inspection.)								
The above well resumed production	on December 6	, 2007 after bein	g off more tha	n 90 days.				
14. I hereby certify that the foregoing is true and correct.								
Name (Printed/Typed)	Title							
G.T. Nimmo	11110		Operations Ma					
Signature / Wund	Date		December 12,	, 2007				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								

Approved by

Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations the operations of the United States any false, fictitiousor traudulent statements or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitiousor traudulent statements or representations as to any matter within its jurisdiction.

	STATE OF UTAH		FORM 9			
			5.LEASE DESIGNATION AND SERIAL NUMBER: SL-045051A			
SUND	RY NOTICES AND REPORTS	ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
	igged wells, or to drill horizontal laterals. I		7.UNIT or CA AGREEMENT NAME: CLAY BASIN			
1. TYPE OF WELL Gas Well		8. WELL NAME and NUMBER: CLAY BASIN UNIT 12				
2. NAME OF OPERATOR: WEXPRO COMPANY			9. API NUMBER: 43009156360000			
3. ADDRESS OF OPERATOR: P.O. Box 458 , Rock Springs,	WY, 82902 307 922-5612	PHONE NUMBER: 2 Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN			
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2210 FSL 2099 FEL			COUNTY: DAGGETT			
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NWSE Section: 22		S	STATE: UTAH			
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPORT,	OR OTHER DATA			
TYPE OF SUBMISSION		TYPE OF ACTION				
	ACIDIZE	ALTER CASING	CASING REPAIR			
✓ NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME			
11/6/2009	DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS, AND MINING  IDRY NOTICES AND REPORTS ON W roposals to drill new wells, significantly deepen existing were plugged wells, or to drill horizontal laterals. Use APPLIC scales.  PHON  In SAID, RANGE, MERIDIAN:  10: 22 Township: 03.0N Range: 24.0E Meridian: S  CHECK APPROPRIATE BOXES TO INDICATE NATURAL RESOURCES  CHANGE WELL STATUS COMM.  CHANGE WELL STATUS COMM.  DEEPEN PRODUCTION START OR RESUME REPERFORATE CURRENT FORMATION SIDETING WATER SHUTOFF SI TAS SIDETING AND	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE			
SUBSEQUENT REPORT	DEEPEN	FRACTURE TREAT	✓ NEW CONSTRUCTION			
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK			
	PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION			
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON			
	☐ TUBING REPAIR	VENT OR FLARE	☐ WATER DISPOSAL			
☐ DRILLING REPORT	☐ WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION			
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:			
12. DESCRIBE PROPOSED OR CO	MPLETED OPERATIONS. Clearly show all pe	rtinent details including dates, depths, v	'			
I .			oldines, etc.			
			Approved by the			
I .			Utah Division of			
			Oil, Gas and Mining			
			ate: November 03, 2009			
			1951 ( ) 111 A			
			y:			
			had diagrams for placement of			
Temperature Elemen			ned diagrams for placement of			
	the Rolli tower	and opecimeation sheets.				
NAME (PLEASE PRINT) Paul Jibson		TITLE Associate Permit Agent				
SIGNATURE N/A		DATE 11/2/2009				

#### WEXPRO COMPANY P.O. BOX 458 ROCK SPRINGS, WY 82902

CLAY BASIN UNIT WELL 12 NWSE 22-3N-24E LEASE NO. SL-045051-a UNIT NO. 892000323B DAGGET COUNTY, UTAH NOTE: THIS LEASE FALLS UNDER THE SITE & SECURITY PLAN ESTABLISHED BY WEXPRO COMPANY. THE PLAN CAN BE REVIEWED AT THE WEXPRO OFFICE IN ROCK SPRINGS WYOMING WEEKDAYS BETWEEN 7:00 AM AND 5:00 PM


#### VALVE LEGEND

#### **TANK # 223**

VALVE # 1 -- OPEN DURING PRODUCTION, SEALED CLOSED DURING SALES

VALVE # 2 -- OPEN DURING SALES, SEALED CLOSED DURING PRODUCTION

VALVE # 3 -- OPEN ONLY TO DRAIN WATER, SEALED CLOSED DURING PRODUCTION



# FloBoss<sup>™</sup>107 Flow Manager.

The FloBoss™ 107 Flow Manager introduces a new technology platform to the FloBoss family of flow computers that raises the bar for modularity, versatility, performance, and ease of use. Whether you need a single or multi-run flow computer or few or many I/O points, the new FloBoss 107 can accommodate your needs. The FloBoss 107 is the ideal measurement solution for many natural gas applications. These include, but are not limited to:


- **■** Custody Transfer
- Wellhead Measurement and Control
- Well Injection Pressure
- Compressor Fuel Gas
- Industrial Gas Usage
- Commercial Gas Usage

The new FloBoss 107 offers you benefits that research has shown flow computer users request. You also get all of the tried and true features of previous FloBoss units such as accurate AGA calculations, data archival, broad communications support, low power consumption, PID loop control, FST control, and operation over extreme temperatures.

API/AGA/ISO Compliant Flow Measurement. The FloBoss 107 maintains API Chapter 21.1 compliant historical archives for measured and calculated values, as well as events and alarms. The firmware has the capability to perform AGA3 orifice flow calculations or AGA7 pulse flow calculations using AGA8 compressibility. It also performs ISO 5167 flow calculations. Other gas flow or properties calculations can be implemented using User C programs.

**One to Four Meter Runs.** The FloBoss 107 features a built-in dual-variable sensor (DVS) port and RTD input for handling a single meter run. For multiple runs, an optional multi-variable sensor (MVS) module supports up to four remote MVS units.

**Scalable and Configurable I/O.** You can add a configurable I/O board to the CPU module and up to three configurable I/O modules to the base FloBoss 107. For even more capacity, add an expansion rack to house up to three additional I/O modules.



FloBoss 107 Base Unit

**Local or Host Operation.** The FloBoss 107 is configured and operated on-site using our Windows® based ROCLINK™ 800 Configuration Software. The FloBoss 107 can also be configured and operated from a computer running popular host software packages. Modbus ASCII and RTU slave or host protocols, as well as native ROC protocol, are supported.


**More Communication Choices.** The FloBoss 107 comes standard with 3 ports: local operator interface, RS-232, and RS-485. One additional port is supported using an expansion communication module.

**Built-in Control Capability.** The FloBoss 107 can perform PID control on 8 loops using analog or discrete outputs. A wide range of control problems can be solved easily and quickly with outstanding results. It can also perform logic and sequencing control by means of Function Sequence Tables (FSTs).



Remote Automation Solutions
Phone (641) 754-3449 Toll Free (800) 807-0730 (US & Canada only)

FAX (641) 754-3630 Website: www.EmersonProcess.com/flow



Base unit (left) provides the backplane, module slots, ports, and electrical interconnections for the FloBoss 107. Dimensions are 204 mm H by 153 mm W by 140 mm D (8 in. H by 6 in. W by 5.5 in. D). Expansion rack (right) plugs into base unit and provides backplane and slots for additional modules. (Same dimensions as base unit).

Local operator interface port (RS-232) communicates to a laptop or similar PC device for local configuration and data retreival.

I/O card is available for the CPU module. Five of the six I/O points are configurable by type (AI/DI, AI/DI, AO/DO, DI/PI, DI/PI) and the sixth is a DO.

CPU module contains the main processing unit, memory, operational firmware, RS-232 port, RS-485 port, and RTD input.

Communication modules are available for a second RS-232 port or RS-485 port.

MVS module supports up to six multi-variable sensor units for differential pressure flow measurement. One MVS module can be used in either slot 4 of the base unit or expansion rack.

I/O modules provide six I/O points (same as I/O card). Up to six I/O modules can be plugged into the FloBoss 107. 24 Vdc loop power is provided.

Module slots accommodate I/O and communication modules and are protected by removable covers when not used.

Covered wiring tray neatly routes field wiring to and from modules.

Battery compartment uses Ilthium battery to backup RAM in the CPU.

Input power range for the FloBoss 107 and I/O is 8 to 30 Vdc.

DVS port provides a serial data link to a dual-variable sensor (DVS) unit.

Display port connects a keypad / display unit to the FloBoss 107. Supports ROC and Modbus slave protocols.

©2006 Fisher Controls International, LLC.

FloBoss and ROCLINK are marks of one of the Emerson Process Management companies. All other marks are the property of their respective owners.

This publication is presented for informational purposes only, and while every effort has been made to ensure its accuracy, its content is not to be construed as a warranty or guarantee, expressed or implied, regarding the products described herein or their use or applicability.



D351406X012 / Printed in USA / 5M / 12-06

#### **MVS205 Multi-Variable Sensor**


The MVS205 Multi-Variable Sensor (version 1.12 or greater) provides static pressure, differential pressure, and process temperature inputs directly to a ROC 300/800 Series Remote Operations Controller or FloBoss™ 407/500 Series Flow Manager. The inputs from an MVS sensor are used in performing differential pressure type calculations. The MVS205 typically operates as a remote unit that communicates via a serial format.

FloBoss 407 units may use a remote or integral MVS205 sensor. ROC300-Series controllers must be equipped with a Remote MVS Interface (CMA8H). FloBoss 500-Series units must be equipped with a Remote MVS Interface (CR1).

#### **Variables**

Functionally, the MVS is a sensor device that measures three flow-related variables simultaneously: differential pressure, static pressure, and temperature. These variables are continuously available to the FloBoss or ROC unit that polls the MVS.

An external three or four-wire RTD is used to sense the process temperature. The RTD sensor is connected directly to the interface circuit board in the MVS sensor housing. User-supplied RTD field wiring is required for the connection.



MVS205 Multi-Variable Sensor

#### **Transducer and Interface Circuit**

The MVS consists of a transducer and an interface circuit. The transducer, contained in the sensor body, uses capacitance-cell technology to sense differential pressure and piezoresistive technology to sense the static (absolute or gauge) pressure.

The transducer electronics convert the pressure variables directly into a digital format, allowing accurate correction and compensation. The raw temperature is converted by the interface board into digital format. A microprocessor linearizes and corrects the raw pressure signals (from the sensor) using characterization data stored in non-volatile memory.

The interface circuit allows the MVS to connect to and communicate with a ROC or FloBoss using a serial EIA-485 (RS-485) connection. In a Remote MVS, this interface circuit board is enclosed in an explosion-proof electronics head.

#### Accuracy

Two versions of the MVS sensor are available: MVS205P with reference accuracy of 0.075% and MVS205E with reference accuracy of 0.10%.

#### Mounting

Attached to the bottom of the sensor body is a Coplanar™ flange. This flange, which provides drain/vent valves, allows the MVS to be mounted on a pipestand, on a wall or panel, or on an integral orifice assembly or manifold valve.

#### **Approvals**

A list of North American approvals can be found in the Specifications table on page 2. For information on the European ATEX approved version, please refer to Specification Sheet 2.5:MVSCE.

D301079X012

#### **Flow Computer Division**





#### **Specifications**

#### **DIFFERENTIAL PRESSURE INPUT**

Range: 0 to 6.22 kPa (0 to 25" H<sub>2</sub>O), 0 to 62.2 kPa (0 to 250" H<sub>2</sub>O), or 0 to 248.8 kPa (0 to 1000" H<sub>2</sub>O).

#### Reference Accuracy:

 $\pm 0.075\%$  of URL (upper range limit) (for MVS205P)  $\pm 0.10\%$  of URL (for MVS205E).

Includes linearity, hysteresis, and repeatability effects for spans up to 10:1 turndown.

Stability: ±0.1% of URL for 12 months.

**Over Pressure Limit:** 250 bar (3626 psi) Applied on either or both sides without damage to the sensor.

#### STATIC PRESSURE INPUT

Range: Either Absolute or Gauge: 0 to 5516 kPa (0 to 800 psia/psig) 0 to 25,000 kPa (0 to 3626 psia/psig)

#### Reference Accuracy:

±0.075% of URL (for MVS205P) ±0.10% of URL (for MVS205E).

Includes linearity, hysteresis, and repeatability effects) for spans up to 6:1 turndown.

Stability: ±0.1% of URL for 12 months. Over Pressure Limit: Same as URL.

#### PROCESS TEMPERATURE INPUT (MVS205 REMOTE ONLY)

**Type:** For 3 or 4-wire platinum 100-ohm RTD (conforming to IEC 751 Class B), with  $\alpha$  = 0.00385.

Range: -40 to 400°C (-40 to 752°F).

Reference Accuracy: ±0.28°C (±0.5°F), exclusive of RTD sensor error. Specification includes linearity, hysteresis, and repeatability effects.

Excitation Current: 1.24 mA.

#### **OUTPUT (MVS205 REMOTE ONLY)**

EIA-485 (RS-485) asynchronous serial communication using Modbus protocol for up to 605 m (2000 ft) distance.

#### **POWER**

Input at 0 to 75°C: 8 to 30 V dc, 245 mW average. Input at -40 to 0°C: 8.5 to 30 V dc, 245 mW average. Supplied by ROC, FloBoss, or Remote MVS Interface.

#### WEIGHT

Including head, 3.0 kg (6.7 lb).

#### **ENVIRONMENTAL**

Operating Temperature: -40 to 75°C (-40 to 167°F). Storage Temperature: -50 to 100°C (-58 to 230°F).

Operating Humidity: 0 to 99%, non-condensing.

#### **DIMENSIONS**

147 mm H by 163 mm W by 84 mm D (5.8 in. H by 6.4 in. W by 3.3 in. D).

#### **VIBRATION EFFECT**

Sensor outputs shall not shift more than +0.1% of upper range limit per g from 5 to 2000 Hz in any axis when tested per IEC 770, Section 6.2.14.

#### CONSTRUCTION

Sensor Body and Coplanar Flange: 316 SST. Wetted Parts: 316 SST is standard; Hastelloy C (NACE compliant) is available. Wetted O-rings are glass-filled TFE.

**Electronics Head (MVS205 Remote):** Urethane-painted die-cast aluminum alloy, rated Type 4X.

#### **MOUNTING (MVS205 REMOTE ONLY)**

**Pipestand:** Mounts on 50 mm (2 in.) pipe with U-bolt and optional flange bracket.

**Wall/panel:** Mounts with optional flange bracket, bolted on 71 mm (2.8 in.) centers.

#### CONNECTIONS

**Conduit:** Head has two 1/2-inch NPT connections. **Process:** 1/4-18 NPT on 2-1/8 inch centers.

#### APPROVALS (MVS205 REMOTE ONLY)

**Evaluated per the Following Standards:** 

CSA C22.2 No. 30. CSA C22.2 No. 213. UL 1203, UL 1604.

**Certified by CSA as**: MVS205R Models RSE or RSP Series.

**Product Markings for Hazardous Locations:** 

Class I, Division 1, Groups C and D.

Class I, Division 2, Groups A, B, C, and D, T5 (T<sub>amb</sub>=70°C), T4 (T<sub>amb</sub>=75°C).

Approved by Industry Canada for use with approved flow computers. Approved as MVS205R Series Remote Sensors (Measurement Canada approval # AG-0412).

Approved by the Alberta Boilers Safety Association: Approval # 0F0792.2


FloBoss is a mark of one of the Emerson Process Management companies. The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their respective owners. The contents of this publication are presented for informational purposes only. While every effort has been made to ensure informational accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. Fisher Controls reserves the right to modify or improve the designs or specifications of such products at any time without notice.

Emerson Process Management Flow Computer Division Marshalltown, IA 50158 U.S.A. Houston, TX 77041 U.S.A. Pickering, North Yorkshire UK Y018 7JA


EMERSON.
Process Management

# pecifications hermosync s

#### **THERMOSYNC MODEL NO. DIMENSIONS**



#### **PROBE**



#### ATP-1000 & ATP-1001 Probe Specifications:

Type:

4-Wire Platinum Wire-Wound

RTD Element

Resistance:

100 Ohms at 0°C (IEC 751)

Alpha Coefficient: .00385 Accuracy:

±0.05°C

Temp. Range:

-40°C to +60°C -40°F to +140°F

Calibration/Accuracy Certification Service Available.

			PROCESS CONN.										
	A	8	С	D	E	F	G	Н	ı	J	К	L	1.1
Part Number													
TAN-1200-L2	12 NPT	1.25°	1/2" NPT	1.69*	0.633	.495	2.22*	1.20	.260°	37	.6451	3.89	901
TAN-1200-L4	1/2" NPT	1.25"	1/2" NPT	1.60*	0.633	495	2.96°	1,20	260"	.37"	.645*	4.75*	.90*
TAN-1200-L0	1/2" NPT	1.25"	1/2" NPT	1.691	0.633	.4861	4.591	1.207	.2601	.37°	645"	6.37	901
TAN-1200-612	1/20 MPT	1.25"	1/2" NPT	1,691	0.633	N/A	6.66*	1.20	.2601	37"	.645"	8.45	.901
TAN-12004L24	UZ* NPT	1.25"	1/2" NPT	1.691	0.633	AM	9.891	1.26	260"	37°	.645°	11.67	901
TAN-3400-L2	10" NPT	1.25	3/4" NPT	1.69°	0.808	,495	2 221	1.20	2601	.37"	.85*	3.62	.90*
TAN-34C3-L4	1/2" NPT	1.25"	3/4" NPT	1.69*	0.808	.4951	2.961	1.207	260"	37"	85	4.561	90"
TAN-3400-UB	10" NPT	1 25"	3/4" NPT	1.691	0.808	.495*	4.59*	1.20"	.2601	.37*	.651	6.201	.901
TAN-94C0-L12	1/2" NPT	1.25"	3/4" NPT	1.691	0.808	NIA	6.66"	1.20°	2601	.37"	85"	8.26*	.90*
TAN-3400-L24	1/2" NPT	1.25"	3/4" NPT	1.691	0.008	N/A	9.89*	1.207	2601	.37"	.65"	1149	.901
TAN-1000-L4	10" NPT	1.375°	1º NPT	1.69*	0.808	.495*	2.96°	1.20	.260"	.37"	.85°	4.75	901
TAN-10C0-L8	1/2" NPT	1.375"	1" NPT	1.69"	0.808	,495°	4.59*	1.20°	2601	.37"	.65"	6.37	.90°
TAN-1000-L12	1/2" NPT	1.375*	1" NPT	1.69°	0.809	N/A	6.66*	1.20	.260*	37"	.85"	8.45	.90*
TAN-10G0-L24	1/2" NPT	1.375	1" NPT	1 69"	0.608	NA	9.89°	1.201	.2001	.37*	.85*	1167	901

**All Thermowells:** 

316L SS Material:

Press/Temp: 4900 PSI Max @ 330° F

Flow:

100 FPS (L2, L4, L8, L12) or 50 FPS

(L24) max in 1000 PSI Natural Gas

Optional Vent/Bleeder Hole Available Additional Plug & Chain Assembly Available NOTE: Use a thermal coupling paste or fluid to couple the probe to the well ONLY in the lower .5 inches of the well. <u>DO NOT</u> fill the well with thermal coupling fluid. Spring load the probe to contact the bottom of the well.

U.S. PATENTED - FOREIGN PATENTS PENDING

TDOC-4 REV.11 1-21-03

Sundry Number: 31178 API Well Number: 43009156360000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOU			FORM 9		
ι	5.LEASE DESIGNATION AND SERIAL NUMBER: SL-045051A					
SUNDR	RY NOTICES AND REPORTS	S ON W	/ELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
	posals to drill new wells, significant reenter plugged wells, or to drill hori n for such proposals.			7.UNIT or CA AGREEMENT NAME: CLAY BASIN		
1. TYPE OF WELL Gas Well				8. WELL NAME and NUMBER: CLAY BASIN UNIT 12		
2. NAME OF OPERATOR: WEXPRO COMPANY				<b>9. API NUMBER:</b> 43009156360000		
3. ADDRESS OF OPERATOR: P.O. Box 458, Rock Spring	s, WY, 82902 307 9	<b>PHONE</b> 922-5612	NUMBER: Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2210 FSL 2099 FEL				COUNTY: DAGGETT		
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 22 Township: 03.0N Range: 24.0E Me	leridian: S		STATE: UTAH		
11. CHECI	K APPROPRIATE BOXES TO INDIC	CATE NAT	URE OF NOTICE, REPOR	RT, OR OTHER DATA		
TYPE OF SUBMISSION			TYPE OF ACTION			
	ACIDIZE	ALTE	ER CASING	CASING REPAIR		
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	СНА	NGE TUBING	CHANGE WELL NAME		
Approximate date work will start.	CHANGE WELL STATUS	Сом	IMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE		
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRAC	CTURE TREAT	☐ NEW CONSTRUCTION		
10/17/2012	OPERATOR CHANGE	PLUG	G AND ABANDON	PLUG BACK		
SPUD REPORT	✓ PRODUCTION START OR RESUME		LAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION		
Date of Spud:	REPERFORATE CURRENT FORMATION		TRACK TO REPAIR WELL	TEMPORARY ABANDON		
	TUBING REPAIR		T OR FLARE	WATER DISPOSAL		
DRILLING REPORT Report Date:	WATER SHUTOFF		A STATUS EXTENSION	APD EXTENSION		
Report Date.		☐ 311 <i>x</i>	A STATUS EXTENSION			
	WILDCAT WELL DETERMINATION	ОТН	ER 	OTHER:		
The above well Res	COMPLETED OPERATIONS. Clearly sho sumed Production on Octo er being off for more than	ber 17,	2012 at 9:45 AM,	Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY October 23, 2012		
NAME (PLEASE PRINT)	PHONE NUM	MBER T	ITLE			
Paul Jibson	307 352-7561	F	Permit Agent			
SIGNATURE N/A			ATE 10/18/2012			

Sundry Number: 34842 API Well Number: 43009156360000 FEDERAL APPROVAL OF THIS ACTION IS NECESSARY

	STATE OF UTAH DEPARTMENT OF NATURAL RESOUR	RCES		5.LEASE DESIGNATION AND SER	FORM 9		
I	SL-045051A	IAL NUMBER:					
	RY NOTICES AND REPORTS		_	6. IF INDIAN, ALLOTTEE OR TRIE	BE NAME:		
Do not use this form for procurrent bottom-hole depth, FOR PERMIT TO DRILL form	oposals to drill new wells, significantly reenter plugged wells, or to drill horiz n for such proposals.	y deepe zontal la	en existing wells below aterals. Use APPLICATION	7.UNIT or CA AGREEMENT NAME: CLAY BASIN			
1. TYPE OF WELL Gas Well				8. WELL NAME and NUMBER: CLAY BASIN UNIT 12			
2. NAME OF OPERATOR: WEXPRO COMPANY				<b>9. API NUMBER:</b> 43009156360000			
3. ADDRESS OF OPERATOR: P.O. Box 458, Rock Spring	ys, WY, 82902 307 92	<b>PHO</b> 1 22-561	NE NUMBER: 2 Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN	:		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2210 FSL 2099 FEL				COUNTY: DAGGETT			
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 22 Township: 03.0N Range: 24.0E Mei	ridian: \$	S	STATE: UTAH			
11. CHEC	K APPROPRIATE BOXES TO INDICA	ATE NA	ATURE OF NOTICE, REPOR	T, OR OTHER DATA			
TYPE OF SUBMISSION			TYPE OF ACTION				
/	ACIDIZE	Па	LTER CASING	CASING REPAIR			
NOTICE OF INTENT Approximate date work will start: 3/15/2013	CHANGE TO PREVIOUS PLANS	С	HANGE TUBING	CHANGE WELL NAME			
3/15/2013	CHANGE WELL STATUS	C	OMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE			
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FF	RACTURE TREAT	NEW CONSTRUCTION			
	OPERATOR CHANGE	PI	LUG AND ABANDON	PLUG BACK			
SPUD REPORT	PRODUCTION START OR RESUME	RI	ECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORM	MATION		
Date of Spud:	REPERFORATE CURRENT FORMATION	SI	DETRACK TO REPAIR WELL	TEMPORARY ABANDON			
	TUBING REPAIR	□ ve	ENT OR FLARE	WATER DISPOSAL			
DRILLING REPORT Report Date:	WATER SHUTOFF	SI	TA STATUS EXTENSION	APD EXTENSION			
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	WILDCAT WELL DETERMINATION	<b>√</b> o	THER	OTHER: Production Equipment			
	COMPLETED OPERATIONS. Clearly show						
	any, requests approval to u		· ·	Accepted by th Utah Division o			
• • • • • • • • • • • • • • • • • • •	ent on the above mentioned nd replaced with a ProPack.		<u> </u>	Oil, Gas and Mini			
l .	will be installed. All new eq			Date: February 25, 2	2013		
	bance and there will be no			Date: Oblidary 20, 2			
	new equipment will be pain			By: Usy Klu	1		
	e existing production equipment						
completion of the new production equipment installation an updated Site Facility Diagram will be submitted to the Vernal BLM Field Office.							
NAME (DI EASE DDINT)	DUONE MIM	IRED	TITLE				
NAME (PLEASE PRINT) Paul Jibson	<b>PHONE NUM</b> 307 352-7561	IDEK	Permit Agent				
SIGNATURE N/A			DATE 2/20/2013				

Sundry Number: 46205 API Well Number: 43009156360000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOUF		FORM 9		
ι	5.LEASE DESIGNATION AND SERIAL NUMBER: SL-045051A				
SUNDR	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:				
Do not use this form for procurrent bottom-hole depth, FOR PERMIT TO DRILL form	7.UNIT or CA AGREEMENT NAME: CLAY BASIN				
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: CLAY BASIN UNIT 12		
2. NAME OF OPERATOR: WEXPRO COMPANY			9. API NUMBER: 43009156360000		
3. ADDRESS OF OPERATOR: P.O. Box 458, Rock Spring	s, WY, 82902 307 9	PHONE NUMBER: 22-5612 Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2210 FSL 2099 FEL			COUNTY: DAGGETT		
QTR/QTR, SECTION, TOWNSH	HIP, RANGE, MERIDIAN: 22 Township: 03.0N Range: 24.0E Me	eridian: S	STATE: UTAH		
11. CHECI	K APPROPRIATE BOXES TO INDICA	ATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA		
TYPE OF SUBMISSION		TYPE OF ACTION			
	ACIDIZE	ALTER CASING	CASING REPAIR		
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME		
7,pp. Oximute date notice and control	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE		
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	NEW CONSTRUCTION		
12/23/2013	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK		
SPUD REPORT	✓ PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION		
Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	TEMPORARY ABANDON		
	TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL		
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION		
	WILDCAT WELL DETERMINATION	OTHER .	OTHER:		
l .	completed operations. Clearly show umed Production on Decen off for more than 90 day	nber 23, 2013, after being			
NAME (5) - 107 - 117		ADED TITLE			
NAME (PLEASE PRINT) Paul Jibson	<b>PHONE NUN</b> 307 352-7561	MBER TITLE Permit Agent			
SIGNATURE N/A		<b>DATE</b> 12/26/2013			

Sundry Number: 57090 API Well Number: 43009156360000

	STATE OF UTAH		FORM 9				
	5.LEASE DESIGNATION AND SERIAL NUMBER: SL-045051A						
SUNDF	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:						
Do not use this form for pro- current bottom-hole depth, FOR PERMIT TO DRILL form	7.UNIT or CA AGREEMENT NAME: CLAY BASIN						
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: CLAY BASIN UNIT 12				
2. NAME OF OPERATOR: WEXPRO COMPANY			9. API NUMBER: 43009156360000				
3. ADDRESS OF OPERATOR: P.O. Box 458, Rock Spring	s, WY, 82902 307 92:	PHONE NUMBER: 2-5612 Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN				
4. LOCATION OF WELL FOOTAGES AT SURFACE:			COUNTY: DAGGETT				
2210 FSL 2099 FEL QTR/QTR, SECTION, TOWNSH Qtr/Qtr: NWSE Section: 2	<b>HIP, RANGE, MERIDIAN:</b> 22 Township: 03.0N Range: 24.0E Meri	dian: S	STATE: UTAH				
11. CHEC	K APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA				
TYPE OF SUBMISSION		TYPE OF ACTION					
	ACIDIZE	ALTER CASING	CASING REPAIR				
NOTICE OF INTENT	CHANGE TO PREVIOUS PLANS	CHANGE TUBING	CHANGE WELL NAME				
Approximate date work will start:	CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE				
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	□ NEW CONSTRUCTION				
10/25/2014	OPERATOR CHANGE	PLUG AND ABANDON	PLUG BACK				
	✓ PRODUCTION START OR RESUME						
SPUD REPORT Date of Spud:	_	RECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION				
	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	LI TEMPORARY ABANDON				
DRILLING REPORT	L TUBING REPAIR	☐ VENT OR FLARE	WATER DISPOSAL				
Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	APD EXTENSION				
	WILDCAT WELL DETERMINATION	OTHER	OTHER:				
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc.  The above well resumed production on October 25, 2014; after being off more than 90 days.  Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONLY October 31, 2014							
NAME (PLEASE PRINT) Paul Jibson	<b>PHONE NUMB</b> 307 352-7561	BER TITLE Permit Agent					
SIGNATURE N/A		<b>DATE</b> 10/28/2014					

Sundry Number: 67526 API Well Number: 43009156360000

	FORM 9					
	5.LEASE DESIGNATION AND SERIAL NUMBER SL-045051A					
SUNDR	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:					
Do not use this form for pro current bottom-hole depth, FOR PERMIT TO DRILL form	7.UNIT or CA AGREEMENT NAME: CLAY BASIN					
1. TYPE OF WELL Gas Well				8. WELL NAME and NUMBER: CLAY BASIN UNIT 12		
2. NAME OF OPERATOR: WEXPRO COMPANY				<b>9. API NUMBER:</b> 43009156360000		
3. ADDRESS OF OPERATOR: P.O. Box 458 , Rock Spring	s, WY, 82902 307 922		NE NUMBER: 2 Ext	9. FIELD and POOL or WILDCAT: CLAY BASIN		
4. LOCATION OF WELL FOOTAGES AT SURFACE: 2210 FSL 2099 FEL				COUNTY: DAGGETT		
QTR/QTR, SECTION, TOWNSH Qtr/Qtr: NWSE Section: 2	HIP, RANGE, MERIDIAN: 22 Township: 03.0N Range: 24.0E Merio	dian: \$	S	STATE: UTAH		
11. CHEC	K APPROPRIATE BOXES TO INDICAT	TE NA	ATURE OF NOTICE, REPOR	T, OR OTHER DATA		
TYPE OF SUBMISSION			TYPE OF ACTION			
	ACIDIZE	Па	LTER CASING	CASING REPAIR		
NOTICE OF INTENT Approximate date work will start:	CHANGE TO PREVIOUS PLANS	С	HANGE TUBING	CHANGE WELL NAME		
	CHANGE WELL STATUS	☐ c	OMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE		
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	☐ FF	RACTURE TREAT	NEW CONSTRUCTION		
10/30/2015	OPERATOR CHANGE	☐ PI	LUG AND ABANDON	PLUG BACK		
SPUD REPORT	✓ PRODUCTION START OR RESUME	☐ RI	ECLAMATION OF WELL SITE	RECOMPLETE DIFFERENT FORMATION		
Date of Spud:	REPERFORATE CURRENT FORMATION	☐ sı	DETRACK TO REPAIR WELL	TEMPORARY ABANDON		
	TUBING REPAIR	☐ vi	ENT OR FLARE	WATER DISPOSAL		
DRILLING REPORT Report Date:	WATER SHUTOFF	☐ sı	TA STATUS EXTENSION	APD EXTENSION		
	WILDCAT WELL DETERMINATION	П o	THER	OTHER:		
44 DECORIDE DRODOCED OD						
	completed operations. Clearly show a disproduction on October 30, more than 90 days.			Accepted by the Utah Division of Oil, Gas and Mining FOR RECORD ONL November 06, 2015	Y	
NAME (PLEASE PRINT) Tammy Fredrickson	<b>PHONE NUMB</b> 307 352-7514	BER	TITLE Senior Permit Agent			
SIGNATURE N/A		-	<b>DATE</b> 11/5/2015			
11//1		- 1	1 1/0/ <b>2</b> 010			